

# DIGITUS Frame set for Keystone Modules

AN-25178  
EAN 4016032302261



### Frame set, 2-level for 6x Keystone Jacks Suitable for OBO-Ackermann GES6

The DIGITUS® Frame sets function as adapter for the installation of Keystone Modules. They are available as 2-level version for 6x Keystone Modules or as 3-level version for 9x Keystone Modules.

### Frame set suitable for Ackermann GES 2, 4, 6, R4, R7

- Layout keystone entry: 45° outlet
- Area of application: Floor box
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:

- Suitable for GES 2, GES 4, GES 4/10, GESR 4, GES 6, GES 6/10, GESR 8/10
- Frame suitable for installation in Ackermann floor box (OBO Bettermann underfloor systems)
- Plug direction of module 45° vertical
- Technical properties:
- Housing material: Metal
- Physical properties:
- Operation temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	15.50	43.00	19.00	34.00	27.78
Packaging Unit Inside	10	1.55	8.00	18.00	17.00	2.45
Packaging Unit Single	1	0.16	3.00	10.00	29.00	870.00
Net single without Packaging	0	0.00	19.00	7.50	2.00	285.00

### More images:



### Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product

- Observe the specifications of the raw cable manufacturer during installation

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)