

DIGITUS Frame set for Keystone Modules

AN-25178
EAN 4016032302261



Frame set, 2-level for 6x Keystone Jacks Suitable for OBO-Ackermann GES6

The DIGITUS® Frame sets function as adapter for the installation of Keystone Modules. They are available as 2-level version for 6x Keystone Modules or as 3-level version for 9x Keystone Modules.

Frame set suitable for Ackermann GES 2, 4, 6, R4, R7

- Layout keystone entry: 45° outlet
- Area of application: Floor box
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:

- Suitable for GES 2, GES 4, GES 4/10, GESR 4, GES 6, GES 6/10, GESR 8/10
- Frame suitable for installation in Ackermann floor box (OBO Bettermann underfloor systems)
- Plug direction of module 45° vertical
- Technical properties:
- Housing material: Metal
- Physical properties:
- Operation temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	15.50	43.00	19.00	34.00	27.78
Packaging Unit Inside	10	1.55	8.00	18.00	17.00	2.45
Packaging Unit Single	1	0.16	3.00	10.00	29.00	870.00
Net single without Packaging	0	0.00	19.00	7.50	2.00	285.00

More images:



Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product

- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com