

DIGITUS mini GBIC (SFP) Module, 1.25 Gbps, 20km

DN-81004
EAN 4016032305729



DN-81004 mini GBIC (SFP) Module, 1.25 Gbps, 20km LC Simplex, Tx1550nm/Rx1310nm, up to 20km

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Ubiquiti, Allied Telesis, Allnet, CISCO, D-Link, Edimax, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, ZyXEL, ZTE, Avaya, Mikrotik, ENTERASYS, FINISAR, FORCE 10, RIVERSTONE, Fortinet
- Bidirectional WDM Module - Only one fiber is needed
- High quality and excellent reliability
- 1.25 Gbps Maximum Data Rate
- Compliant to IEEE 802.3z Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation



- MSA (Multi Source Agreement) compliant
- Hot pluggable
- Connector: 1x LC Simplex
- Wavelength: Tx 1550nm / Rx 1310nm
- Transmission Power: Minimum -5 dBm, Maximum 0 dBm
- Sensitivity receiving power: minimum -24 dBm
- For a Distance of up to 20km
- Suitable for 09/125µm Singlemode Fiber Cables
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: 0 °C ~ 70 °C
- Mod: Jednomodni
- Priključak: LC
- Udaljenost (km): 20
- Valna duljina: 1550/1310 nm
- DDM podrška: Ne
- Kompatibilnost proizvođača: Univerzalni (MSA), Cisco
- Način emitiranja: Dvosmjerno
- Ethernet brzina: Gigabit

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	240	8.50	50.00	29.00	54.50	79.03
Packaging Unit Inside	30	1.06	7.00	20.00	30.00	4.20
Packaging Unit Single	1	0.04	9.00	11.50	3.00	310.50
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:



Part Number	Rate	Speed	Distance	Connector	Mounting	Operating Temperature	Industrial Model
SFP Modules							
Plastic Housing							
Di-4140	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4141	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4142	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4143	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Plastic Housing							
Di-4144	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4145	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4146	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4147	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4148	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4149	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4150	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4151	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4152	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4153	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4154	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4155	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4156	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4157	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4158	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4159	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4160	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4161	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4162	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4163	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4164	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4165	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4166	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4167	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4168	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4169	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4170	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4171	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4172	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4173	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4174	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4175	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4176	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4177	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4178	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4179	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4180	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4181	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4182	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4183	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4184	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4185	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4186	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4187	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4188	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4189	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4190	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4191	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4192	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4193	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4194	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4195	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4196	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4197	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4198	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4199	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	
Di-4200	40Gbps	10 Gbps	10km	LC	Standard	0 to 70 °C	