

DIGITUS mini GBIC (SFP) Module, 10Gbps, 0.3km, with DDM Feature

DN-81200
EAN 4016032324133



10G SFP+ Module, Multimode, DDM LC Duplex Connector, 850nm, up to 300m

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Supports DDM (Digital Diagnostic Monitoring)
- High quality and excellent reliability
- 10 Gbps Maximum Data Rate
- Compliant to IEEE802.3ae 10 Gigabit Standard
- Class 1 laser product compliant with EN 60825-1

- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable
- Connector: 1x LC Duplex
- Wavelength: 850nm
- Transmission Power: Minimum -5 dBm, Maximum -1 dBm
- Empfangsensitivität: Minimum -11,5 dBm
- For a distance of up to 0.3km
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: 0 °C ~ 70 °C
- Mode: Multimode
- Connector: LC
- Distance (km): 0.3
- Wavelength: 850 nm
- DDM Support: yes
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Cisco
- Ethernet speed: 10 Gigabit

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	0.80	41.00	26.00	16.00	17.06
Packaging Unit Inside	1	0.04	3.00	11.50	9.00	310.50
Packaging Unit Single	1	0.04	3.00	11.50	9.00	310.50
Net single without Packaging	0	0.03	5.50	1.20	0.80	5.28

More images:

SFP Modules							
Part Number	Data Rate	Speed	Distance	Connector	Wavelength	Operating Temperature	Reliability Feature
DS-4001	4000000000	100 Gbps	10 km	LC Duplex	1030nm	-40 to 70 °C	
DS-4002	4000000000	100 Gbps	300 m	LC Duplex	1030nm	-40 to 70 °C	
DS-4003	4000000000	100 Gbps	300 m	LC Duplex	1030nm	-40 to 70 °C	
QSFP							
DS-4004	4000000000	100 Gbps	300 m	LC Duplex	1030nm	-40 to 70 °C	
DS-4005	4000000000	100 Gbps	300 m	LC Duplex	1030nm	-40 to 70 °C	
DS-4006	4000000000	100 Gbps	300 m	LC Duplex	1030nm	-40 to 70 °C	
DS-4007	4000000000	100 Gbps	300 m	LC Duplex	1030nm	-40 to 70 °C	
DS-4008	4000000000	100 Gbps	300 m	LC Duplex	1030nm	-40 to 70 °C	
DS-4009	4000000000	100 Gbps	300 m	LC Duplex	1030nm	-40 to 70 °C	
10G							
DS-1000	10000000000	10 Gbps	300 m	LC Duplex	1310nm	-40 to 70 °C	
DS-1001	10000000000	10 Gbps	300 m	LC Duplex	1310nm	-40 to 70 °C	
Fast Ethernet							
DS-1012	10000000000	10 Gbps	300 m	LC Duplex	1310nm	-40 to 70 °C	✓
DS-1014	10000000000	10 Gbps	300 m	LC Duplex	1310nm	-40 to 70 °C	✓
DS-1015	10000000000	10 Gbps	300 m	LC Duplex	1310nm	-40 to 70 °C	✓
DS-1016	10000000000	10 Gbps	300 m	LC Duplex	1310nm	-40 to 70 °C	✓
DS-1017	10000000000	10 Gbps	300 m	LC Duplex	1310nm	-40 to 70 °C	✓
DS-1018	10000000000	10 Gbps	300 m	LC Duplex	1310nm	-40 to 70 °C	✓
DS-1019	10000000000	10 Gbps	300 m	LC Duplex	1310nm	-40 to 70 °C	✓
DS-1020	10000000000	10 Gbps	300 m	LC Duplex	1310nm	-40 to 70 °C	✓

