

# DIGITUS Komunikacijski ormar Dynamic Basic - 600x600 mm (ŠxD)

DN-19 42U-6/6-D  
EAN 4016032336464



## ORMAR 42U 60/60 DN-19-42U-6/6-D

Dynamic Basic komunikacijski ormari dizajnirani su i proizvedeni za ugradnju i ožičenje aktivne i pasivne mrežne opreme. S nekoliko optimizacija možete osigurati savršen odnos kvalitete i dodane vrijednosti. Svaki ormar ima čvrstu konstrukciju, jednostavan je za uporabu i estetski prihvatljiv svakom prostoru. Prednja vrata izrađena su od bočnih metalnih profila sa sigurnosnim staklom. Svi bočni paneli kao i stražnji panel mogu se zaključati i ukloniti po potrebi. Svaki ormar je opremljen s galvaniziranim 483 mm (19") šinama koje su montirane s lijeve i desne strane, s prednje i sa stražnje strane ormara. Mogu se prilagoditi po dubini i na njima se nalaze oznake visine po broju unita. Krov je pripremljen za ugradnju ventilatorskih jedinica. Svi Dynamic Basic komunikacijski ormari isporučeni su kompletno sastavljeni. Dostupni su u različitim visinama od 22U do 47U i širine od 600 ili 800 mm, dubine od 600 do 800 mm. Dolaze u standardnim bojama, sivoj (RAL 7035) i crnoj (RAL 9005). Ostale boje dostupne su na zahtjev.

**The DIGITUS® Dynamic Basic Series is made for high demand IT-Infrastructure Solutions - designed and developed on highest standard in Germany**

- Safety class rating IP20
- Lateral metal struts front door with safety glass
- Lock system with pivot lever on front door
- 120° door opening angle on the front door
- 1-point-locking-mechanism on the front door
- Rear wall and side panels are lockable and detachable
- incl. 4 pieces of leveling feet already pre-configured under the rack

- 483 mm (19") profile rails mounted on the front- and rear side inside of the rack, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height unit marking
- Base with punched out cable entry, covered with screwed metal plate
- Roof with punched out cable entries with plastic covers
- Roof is prepared for fan units (punched out entries)
- Several earthing points for rack components
- Incl. installation set (screws, cage nuts, washers)
- Rack is completely mounted
- Equipment mounting depth min.-max.: 290-550 mm
- Bočne ploče: Obje strane
- Boja: svijetlo siva, RAL 7035
- Dubina: 600 mm
- Jedinice: 42
- Kapacitet opterećenja: 600 kg
- Prednja vrata: Staklena vrata, jednostruko otvaranje
- Širina: 600 mm
- Stražnja vrata: Stražnja ploča s bravom, odvojiva
- Vrsta ormara: Mrežni ormar
- IP klasa zaštite: IP20
- Montirano: Da

### Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- 2 x keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	1	73.00	65.00	65.00	209.00	883.03
Packaging Unit Inside	1	73.00	65.00	65.00	209.00	883.03
Packaging Unit Single	1	73.00	65.00	65.00	209.00	883.03
Net single without Packaging	0	72.00	60.00	60.00	204.00	734.40

**More images:**

