

DIGITUS Komunikacijski ormar Dynamic Basic - 600x800 mm (ŠxD)

DN-19 22U-6/8-D
EAN 4016032336471



ORMAR 22U 60/80 DN19-22 STOJ-D 1155x600x800 mm, color grey (RAL 7035)

Dynamic Basic komunikacijski ormari dizajnirani su i proizvedeni za ugradnju i ožičenje aktivne i pasivne mrežne opreme. S nekoliko optimizacija možete osigurati savršen odnos kvalitete i dodane vrijednosti. Svaki ormar ima čvrstu konstrukciju, jednostavan je za uporabu i estetski prihvatljiv svakom prostoru. Prednja vrata izrađena su od bočnih metalnih profila sa sigurnosnim staklom. Svi bočni paneli kao i stražnji panel mogu se zaključati i ukloniti po potrebi. Svaki ormar je opremljen s galvaniziranim 483 mm (19") šinama koje su montirane s lijeve i desne strane, s prednje i sa stražnje strane ormara. Mogu se prilagoditi po dubini i na njima se nalaze oznake visine po broju unita. Krov je pripremljen za ugradnju ventilatorskih jedinica. Svi Dynamic Basic komunikacijski ormari isporučeni su kompletno sastavljeni. Dostupni su u različitim visinama od 22U do 47U i širine od 600 ili 800 mm, dubine od 600 do 800 mm. Dolaze u standardnim bojama, sivoj (RAL 7035) i crnoj (RAL 9005). Ostale boje dostupne su na zahtjev.

The DIGITUS® Dynamic Basic series has been manufactured, designed and developed to meet the high demands of IT infrastructure

- Protection class IP20
- Front door made of metal side struts with safety glass
- Locking system with swivel lever handle on front door
- 120° door opening angle
- 1-point locking on the front door
- Rear and side panels are lockable and removable
- Incl. 4 levelling feet, enclosed

- 483 mm (19") profile rails mounted at the front and rear inside the enclosure, galvanized
- 483 mm (19") profile rails are adjustable in depth and marked with the height unit
- Base with punched cable inlet, covered with screwed plate
- Die-cut cable inlets with plastic cover in the roof
- Roof is prepared to accommodate a fan element (punched-out mounts)
- Various earthing points in the enclosure for built-in components
- Incl. installation set (screws, cage nuts, washers)
- Supplied fully assembled
- Installation depth for components min. - max.: 430-750 mm

Attributes

- Bočne ploče: Objе strane
- Boja: svijetlo siva, RAL 7035
- Dubina: 800 mm
- Jedinice: 22
- Kapacitet opterećenja: 600 kg
- Prednja vrata: Staklena vrata, jednostruko otvaranje
- Širina: 600 mm
- Stražnja vrata: Stražnja ploča s bravom, odvojiva
- Vrsta ormara: Mrežni ormar
- IP klasa zaštite: IP20
- Montirano: Da

Package contents

- Earthing cable set
- Installation set (screws, cage nuts, washers)
- 2 x key

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	44.00	85.00	65.00	120.50	665,762.00
Packaging Unit Inside	1	44.00	85.00	65.00	120.50	665,762.00
Packaging Unit Single	1	44.00	85.00	65.00	120.50	665,762.00
Net single without Packaging	0	43.00	80.00	60.00	115.50	554.40

More images:**Safety notes**

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be neatly routed and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com