

DIGITUS Network cabinet Unique series - 800x800 mm (WxD)

DN-19 26U-8/8-1
EAN 4016032353515



ORMAR 26U 80/80 -1 RAL 7035 1342x800x800 mm, color grey (RAL 7035)

The network cabinets in the Unique series have been developed for particularly convenient and flexible network cabling. Brush-equipped inlets in the top and base (from 26U and 800 mm cabinet width), a slide-on inlet in the base chassis with foam rubber seal and rear brush strips above and below the rear door (from 26U) enable versatile use in a wide range of application scenarios. Vertical cable ducts with cover, installed next to the profile rails (from 800 mm enclosure width), round off the design. An offset, removable cover with ventilation slots ensures improved air circulation. This sits over a special construction for easy mounting of a fan module. Two pairs of galvanized 483 mm (19") profile rails, labelled with height units that can be read in both directions, are installed inside. They can be adjusted in depth and are connected to additional depth braces in the enclosure. Each enclosure is a robust steel construction made from sheet steel up to 1.5 mm thick. The coloring takes the form of electrostatic powder coating in the standard colors grey (RAL 7035) and black (RAL 9005). Modular lockable and removable side panels and doors improve accessibility. Door hinges can be changed. Furthermore, the cabinets can be completely dismantled if required thanks to the demountable design.

The DIGITUS® Unique series has been manufactured, designed and developed for the high demands of IT infrastructure.

- Protection class IP20
- Front door made entirely of metal frame with safety glass
- Locking system with swivel lever handle on front door (prepared to accept profile half cylinder; adapter included)
- 120° door opening angle of the front and rear doors
- Double-leaf rear door
- 1-point locking on all doors
- Side panels are lockable and removable
- Incl. 4 levelling feet, enclosed

- 483 mm (19") profile rails mounted at the front and rear inside the enclosure, galvanized
- 483 mm (19") profile rails are adjustable in depth and marked with the height unit
- Built-in depth struts provide stability
- Slide-on cable inlet with foam rubber seal in the base
- Cable inlet with brush strip at the top and bottom rear of the enclosure
- Cable inlet in the floor and roof with brush strip on the left and right
- Roof is prepared to accommodate a fan unit and an attached, removable cover
- Various earthing points in the enclosure for built-in components
- Incl. installation set (screws, cage nuts, washers)
- Supplied fully assembled
- Installation depth for components min.-max.: 563-743 mm
- Front vertical cable routing panel
- Bočne ploče: Objе strane
- Boja: svijetlo siva, RAL 7035
- Dubina: 800 mm
- Jedinice: 26
- Kapacitet opterećenja: 800 kg
- Prednja vrata: Staklena vrata, jednostruko otvaranje
- Širina: 800 mm
- Stražnja vrata: Čelična vrata i ulaz za kabele, dvostruko otvaranje
- Vrsta ormara: Mrežni ormar
- IP klasa zaštite: IP20
- Montirano: Da

Package contents

- Earthing cable set
- Installation set (screws, cage nuts, washers)
- Installation kit for profile half cylinder
- 2 x key

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	82.00	85.00	85.00	139.20	1,005,720.00
Packaging Unit Inside	1	82.00	85.00	85.00	139.20	1,005,720.00
Packaging Unit Single	1	82.00	85.00	85.00	139.20	1,005,720.00
Net single without Packaging	0	81.00	80.00	80.00	134.20	858.88

More images:

