

DIGITUS Zidni komunikacijski ormari IP55 - 600x450 mm (ŠxD)

DN-19 12U-I-OD
EAN 4016032360995



ORMAR 12U za vanjsku montažu IP55 705x670x450 713x600x450 mm, color grey (RAL 7035)

IP 55 ormari za vanjsku montažu 483 mm (19") dizajnirani su primjenu u industriji. Proizvedeni su u stupnju zaštite IP55 sukladno EN 60529 i time su zaštićeni od ulaska vode i nečistoća. Ventilator i filter su proizvedeni u stupnju zaštite IP54. Najbolje performanse su osigurane sa sustavom zaključavanja u 3 točke sa zakretnom ručkom za zaključavanje i izoliranim ulazima za kabele. Integrirani ventilacijski ulazi osiguravaju ulazak svježeg zraka (stupanj zaštite IP54). Ovi ormari koriste se na otvorenim prostorima (utjecaj kiše, prašine, susnežice, snijega i prskajuće vode).

The DIGITUS® IP55 Outdoor Wall Mounting Cabinets are designed for industrial applications with protection against water and dust acc. to safety class IP55.

- Safety class rating IP 55
- Lockable steel front door with pivot lever
- 140° door opening angle
- 3-point-locking-mechanism on the front door
- Front door with earthing lead and two welded, strengthening bars in U-shape as well as gasketing system
- 483 mm (19") profile rails mounted on the front side inside of the cabinet, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height unit marking
- 1.5 mm strong sheet steel with a high loading capacity, powder coated

- Single welded housing for more strength
- Cable entries in base: 2x M32, 1x M63, 2x PVC blind cap (with diameter of 28 mm)
- Roof canopy offers protection for suitable fan units and takes care of deaeration and hot air
- incl. 4 pcs. mounting brackets, 3 mm strong, as well as suitable screws and washers, for wall mounting
- incl. 4 pcs. mounting brackets, 3 mm strong, as well as suitable screws and washers, for wall mounting
- Equipment mounting depth min.-max.: 142-342 mm
- Distance of installation holes to wall mount (H x W) in mm: 520 x 550
- Boja: svijetlo siva, RAL 7035
- Dubina: 450 mm
- Jedinice: 12
- Kapacitet opterećenja: 100 kg
- Prednja vrata: Čelična vrata, zatvorena, jednostruko otvaranje
- Širina: 600 mm
- Vrsta ormara: Zidni ormarić, vanjski
- IP klasa zaštite: IP55
- Montirano: Da

Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- 2 x Keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	38.00	50.00	65.00	76.30	247.98
Packaging Unit Inside	1	38.00	50.00	65.00	76.30	247.98
Packaging Unit Single	1	38.00	50.00	65.00	76.30	247.98
Net single without Packaging	0	37.00	45.00	60.00	71.30	192.51

More images:



Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be laid neatly and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com