

DIGITUS Zidni komunikacijski ormari IP55 - 600x450 mm (ŠxD)

DN-19 16U-I-OD
EAN 4016032362128



ORMAR 16U 600/450 IP55 za vanjsku montažu 891x600x450 mm, color grey (RAL 7035)

IP 55 ormari za vanjsku montažu 483 mm (19") dizajnirani su za primjenu u industriji. Proizvedeni su u stupnju zaštite IP55 sukladno EN 60529 i time su zaštićeni od ulaska vode i nečistoća. Ventilator i filter su proizvedeni u stupnju zaštite IP54. Najbolje performanse su osigurane sa sustavom zaključavanja u 3 točke sa zakretnom ručkom za zaključavanje i izoliranim ulazima za kabele. Integrirani ventilacijski ulazi osiguravaju ulazak svježeg zraka (stupanj zaštite IP54). Ovi ormari koriste se na otvorenim prostorima (utjecaj kiše, prašine, susnježice, snijega i prskajuće vode).

The DIGITUS® IP55 Outdoor Wall Mounting Cabinets are designed for industrial applications with protection against water and dust acc. to safety class IP55.

- Safety class rating IP 55
- Lockable steel front door with pivot lever
- 140° door opening angle
- 3-point-locking-mechanism on the front door
- Front door with earthing lead and two welded, strengthening bars in U-shape as well as gasketing system
- 483 mm (19") profile rails mounted on the front side inside of the cabinet, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height unit marking

- 1.5 mm strong sheet steel with a high loading capacity, powder coated
- Single welded housing for more strength
- Cable entries in base: 2x M32, 1x M63, 2x PVC blind cap (with diameter of 28 mm)
- Roof canopy offers protection for suitable fan units and takes care of deaeration and hot air
- Integrated air ventilation inlets ensure the entry of fresh air
- incl. 4 pcs. mounting brackets, 3 mm strong, as well as suitable screws and washers, for wall mounting
- Equipment mounting depth min.-max.: 142-342 mm
- Distance of installation holes to wall mount (H x W) in mm: 698 x 550
- Boja: svijetlo siva, RAL 7035
- Dubina: 450 mm
- Jedinice: 16
- Kapacitet opterećenja: 100 kg
- Prednja vrata: Čelična vrata, zatvorena, jednostruko otvaranje
- Širina: 600 mm
- Vrsta ormara: Zidni ormarić, vanjski
- IP klasa zaštite: IP55
- Montirano: Ne

Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- 2 x Keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	42.00	50.00	65.00	94.10	305.83
Packaging Unit Inside	1	42.00	50.00	65.00	94.10	305.83
Packaging Unit Single	1	42.00	50.00	65.00	94.10	305.83
Net single without Packaging	0	41.00	45.00	60.00	89.10	240.57

More images:

