

DIGITUS Unique serverski ormari - 800x1200 mm (ŠxD)

DN-19 SRV-42U-8/12B
EAN 4016032364344



ORMAR 42U 80/120 SERVERSKI:RAL 9005 perforated steel doors, color black (RAL 9005)

Unique serverski ormari dizajnirani su i proizvedeni za sigurnu ugradnju serverske opreme. S nekoliko optimizacija možete osigurati savršen odnos kvalitete i dodane vrijednosti. Svaki ormar ima čvrstu konstrukciju, jednostavan je za uporabu i estetski prihvatljiv svakom prostoru. Serverski Unique ormari idealni su za serverske sobe manjih i srednjih dimenzija te za instalaciju u data centrima. Ormar se sastoji od okvira modularne konstrukcije koji osigurava čvrstoću. Ključne karakteristike ove ponude su protočnost zraka zahvaljujući visokom stupnju perforacija (63%) i upravljanje hlađenjem (ventilacija). Opremi u svakom ormaru možete jednostavno pristupiti zahvaljujući brzom i jednostavnom sistemu zaključavanja bočnih panela kao i prednjih i stražnjih vrata. Šine 483 mm (19") podesive su po cijeloj dubini ormara. Osim toga, bočni nosači montirani između njih osiguravaju dodatnu čvrstoću ormara. Prednja vrata opremljena su s mehanizmom za zaključavanje u četiri točke, a stražnja vrata opremljena su s mehanizmom za zaključavanje u tri točke. Dostupni su u različitim visinama od 26U do 47U i širine od 600 ili 800 mm, dubine od 600, 1000 ili 1200 mm. Dolaze u standardnim bojama, sivoj (RAL 7035) i crnoj (RAL 9005). Ostale boje dostupne su na zahtjev.

The DIGITUS® Unique Series is made for high demand IT-Infrastructure Solutions - designed and developed on highest standard in Germany

- Safety class rating IP20
- Front- and rear doors made out of 70% perforated steel
- Front door is curved to the outside in perforated resp. plexi glass area
- Lock system with pivot lever on front- and rear door (incl. profile half cylinder lock)
- 230° door opening angle on front- and rear doors
- Double wing opening rear door
- Front door with 4-point locking and rear door with 3-point locking

- Horizontally separated side panels (two per side), lockable and detachable
- incl. 4 pieces of leveling feet and 4 pieces of castor, already pre-configured under the cabinet (front castor are lockable)
- 483 mm (19") profile rails mounted on the front- and rear side inside of the rack, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height unit marking
- Built-in depth support bars for more stability
- Sliding cable entry with rubber sealing on the top and base
- Top and base with brushed cable entries left and right
- Special roof construction for fan unit, incl. perforated cover
- Incl. installation set (screws, cage nuts, washers)
- Rack is completely mounted
- Packaging dimensions (HxWxD): 2110x880x1300 mm
- Weights: 144 kg (net); 157 kg (gross)
- Equipment mounting depth min.-max.: 150-1070 mm
- Bočne ploče: Objе strane
- Boja: crna, RAL 9005
- Dubina: 1200 mm
- Jedinice: 42
- Kapacitet opterećenja: 1000 kg
- Prednja vrata: Čelična vrata, perforirana, jednostruko otvaranje
- Širina: 800 mm
- Stražnja vrata: Čelična vrata, perforirana, dvostruko otvaranje
- Vrsta ormara: Ormar za mrežnog poslužitelja
- IP klasa zaštite: IP20
- Montirano: Da

Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- Installation Kit for Profile Half Cylinder
- 2 x Keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	145.00	125.00	85.00	205.00	2,178,120.00
Packaging Unit Inside	1	145.00	125.00	85.00	205.00	2,178,120.00
Packaging Unit Single	1	145.00	125.00	85.00	205.00	2,178,120.00
Net single without Packaging	0	144.00	120.00	80.00	200.00	1,920,000.00

More images:

