

DIGITUS CAT 6 S/FTP outdoor patch cord, PE

DK-1644-010/BL-OD
EAN 4016032371311



CAT 6 S-FTP outdoor patch cord, Cu, PE AWG 27/7, length 1 m, black sheath color

The DIGITUS® Category 6 Class E patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 6 cabling. The performance is tested up to 250 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. With its UV resistant PE sheath, this outdoor patch cord will ensure a secure installation in areas with a lot of temperature fluctuation and sun exposure. Furthermore the drain wire will work as a lightning arrester.

Best performance and link quality for your network with UV resistance.

- 2x RJ45 (8P8C) connectors
- Boots with kink protection, strain reliefs and latch protection
- Length marking on boot
- Conductor: Copper (Cu)
- UV resistant, acid- & alkali resistant, corrosion resistant
- Operating temperature: -20 °C up to +60 °C
- Assortment: Twisted Pair Patch Cables
- Configuration: 1:1
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Packaging: DIGITUS Polybag
- Category: CAT 6
- Shielding: S-FTP, pairs in metal foil and braid shielding
- Length: 1 m
- Color: black
- Jacket: PE
- Slim Version: no
- Structure: 4 x 2 AWG 27/7, twisted pair
- Flat Version: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	180	7.38	46.00	33.00	28.00	42.50
Packaging Unit Inside	10	0.41	11.00	25.00	30.00	8.25
Packaging Unit Single	1	0.04	1.60	14.00	25.00	560.00
Net single without Packaging	0	0.04	100.00	1.17	1.27	148.59

More images:

