

# DIGITUS 1.25 Gbps copper SFP-module, RJ45

DN-81005  
EAN 4016032389484



### 1.25 Gbps Copper SFP Module, RJ45 10/100/1000Base-T, up to 100m

The DIGITUS® Mini GBIC (SFP) transceiver modules offer the highest quality and reliability. The module offers a perfect opportunity for you to extend your Gigabit network switch with a free SFP Uplink Port around an additional RJ45 connection. Thanks to the hot-plug capability, you can install the module without any interruption to the network traffic or restart of the device. In addition, conformity with the MSA (Multi Source Agreement) standard provides compatibility with the current network switch manufacturers.

#### The plug and play extension for your network switch

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Up to 1.25 Gbps bidirectional maximum data rate

- Compliant to IEEE 802.3z Gigabit Standard
- High quality and excellent reliability
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable - installation possible while in operation
- Auto MDI/MDI-X
- Connection: 1x RJ45, CAT 5
- Distance: up to 100 m
- Operating temperature: 0 °C ~ 70 °C
- Mode: Copper
- Connector: RJ45
- Distance (km): 0.1
- DDM Support: no
- Manufacturer compatibility: Universal (MSA)
- Ethernet speed: Gigabit

#### Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	120	7.00	25.40	39.40	55.00	55,041.80
Packaging Unit Inside	30	1.75	7.00	20.00	30.00	4.20
Packaging Unit Single	1	0.06	3.20	9.30	12.00	357.12
Net single without Packaging	0	0.02	1.50	1.50	7.00	15.75

More images:



SFP Modules							
Product Number	MM Code	Speed	Distance	Connector	Mounting	Operating Temperature	Industrial Version
<b>Fast Ethernet</b>							
DM-0101	42780000040	100 Mbps	2 km	LC-Multifiber Duplex	19mm	0 to +70 °C	✓
DM-0102	42780000070	100 Mbps	55 km	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0104	42780000070	100 Mbps	55 km	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
<b>10 Gigabit</b>							
DM-0105	42780000080	10 Gbit	100 m	LC-Multifiber Duplex	19mm	0 to +70 °C	✓
DM-0106	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0107	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0108	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0109	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0110	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0111	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0112	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0113	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0114	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0115	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0116	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0117	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0118	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0119	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓
DM-0120	42780000080	10 Gbit	200 m	LC-BiDirectional Duplex	19mm	0 to +70 °C	✓