

# DIGITUS USB 3.1 Type-C™ - SATA 3 adapter cable for 2.5" SSDs/HDDs

DA-70327  
EAN 4016032390565



**SATA Adapter Cable USB Type-C to SATA III, chipset: NS1068X, 5Gbps**

The Digitus USB 3.1 Type-C™ - SATA 3 adapter cable enables quick and easy access to your 2.5" SATA III SSDs/HDDs via the USB 3.1 Type-C™ port on your PCs/notebooks. Thanks to the USB 3.1 (Gen 1) interface, extremely fast data transfer rates of up to 6 Gbit/s are ensured. This also provides UASP support for improved performance. It does not require additional power supply, the power supply is ensured via the USB port.

**Faster and easier access to your 2.5" SATA III SSDs/HDDs via the USB 3.1 Type-C™ port on your PCs/notebooks**

- Faster and easier access to your 2.5" SATA III SSDs/HDDs via the USB 3.1 Type-C™ port on your PCs/notebooks
- Connector 1: USB 3.1 Type-C™
- Connector 2: SATA (22 pin)
- Supports 2.5" SATA I-III SSDs/HDDs
- USB 3.1 (Gen 1) - data transfer rate of up to max. 5 Gbit/s

- Supports UASP (USB Attached SCSI Protocol)
- SATA III - data transfer rate of up to max. 6 Gbit/s
- Support capacity: up to 5 TB
- Chipset: NS1068X
- Supports hot-plugging and is plug & play capable
- Power supply via USB port
- Supports: Win 10 (64 bit), 10, 8.1 (64 bit), 8.1, 8 (64 bit), 8, 7 (64 bit), 7, Mac OS 10.11 or higher, Linux Kernel 3.19 or higher, Google Chrome OS
- Cable length: 35 cm
- Weight: 20 g
- Color: Black

**Attributes**

- USB-C Products: yes

**Package contents**

- USB 3.1 Type-C™ - SATA 3 adapter cable for 2.5" SSDs/HDDs
- User manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	200	10.90	38.10	30.20	31.10	35,784.30
Packaging Unit Inside	1	0.05	8.00	12.00	1.50	144.00
Packaging Unit Single	1	0.05	8.00	12.00	1.30	124.80
Net single without Packaging	0	0.02	21.50	4.50	1.10	106.43

**More images:**



**Safety notes**

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)