

DIGITUS Kabel za izradu prespojnih kabela, CAT 6A U/FTP

DK-1623-A-P-305
EAN 4016032426004



CAT 6A U-FTP patch cable, raw length 305 m, paper box, AWG 27/7,

Kabeli za izradu prespojnih kabela proizvedeni su i testirani sukladno ISO/IEC 11801 i DIN EN 50173 specifikacijama. Oni garantiraju sukladnost instaliranog sistema kabliranja sa ISO & EN zahtjevima stalne veze i time omogućavaju optimalno kabliranje sustava. Kabeli za izradu prespojnih kabela prikladni su za montažu RJ45 mikroutikača.

Vrhunsku kvalitetu Vaše mreže osigurava oprema izrađena po standardima orijentiranim budućim zahtjevima.

- Izolacija: HD-PE
- Promjer vanjskog plašta: Nominalni 0,55 mm
- Ukupni promjer: Nominalni 5,8 mm
- Vučno opterećenje: 150 N maks.
- Statički radijus savijanja: 4x AD mm min.
- Dinamički radijus savijanja: 8x AD mm min.
- Raspon temperatura za prijevoz i skladištenje: -10 °C do +75 °C
- Raspon radne temperature: -10 °C do +60 °C
- Temperaturni raspon instalacije: 0°C do +50°C
- Otpor DC petlje: ≤ 280 Ω km
- Nebalansirani otpor ≤ 2%
- Otpor izolacije: ≥ 2000MΩ/km @500V
- Kapacitet: nom. 48 nF/km @ 800 Hz
- Nebalansirani kapacitet (parica-uzemljenje): ≤ 1500 nF/km
- Karakteristika impedancije: 100 ± 15 Ω @ 10-100 MHz

- NVP: 67%
- Kašnjenje signala: nom. ≤ 555 ns/100 m
- Odgoda: nom. ≤ 50 ns/ 100 m
- Testni napon (DC 1 min) jezgra/jezgra: 1000 V
- Prigušenje spoja: ≥ 40 dB
- Kapacitet: 48 pF/m nominalni @ 800 Hz
- Nebalansirani kapacitet (parica-uzemljenje): 1,5 pF/m maks @ 1 KHz
- Otpor izolacije: 2 GΩ x km min.
- Otpor DC petlje: 147 Ω/km maks. (2% maks. nebalansirani otpor)
- Napon: 72 Vdc maks.
- Prigušenje spoja: 40 dB
- Kašnjenje: 450 nS/100 m maks.
- Kašnjenje signala: 20 nS/100 m maks.

Attributes

- Asortiman: Patch kabeli s upredenim paricama
- Kategorija: CAT 6A
- Oklop: U-FTP, parovi u metalnoj foliji
- Duljina: 305 m
- Boja: sivi
- Kapica: LSOH
- Struktura: 4 x 2 AWG 27/7, upletena parica
- Tanka verzija: Ne
- Flat Version: Ne

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	2	18.50	42.50	45.00	45.00	86,062.50
Packaging Unit Inside	1	9.25	39.00	39.00	20.00	30.42
Packaging Unit Single	1	9.25	39.00	39.00	20.00	30.42
Net single without Packaging	0	8.00	30.50	5.80	5.80	1,026,020.00

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.

- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com