

# DIGITUS USB-C 3.1 Gen2 connection cable, USB-C to USB-C

AK-300139-010-S  
EAN 4016032426011



**USB Type-C connection cable, type C to C M/M, 1.0m, full featured, Gen2, 5A, 10GB,**

For connecting external USB devices (with C socket, e.g. PC, tablet or smartphone) to the USB host (e.g. PC, notebook). Data transfer rate up to 10 Gbit/s (Superspeed+).

**One cable for Data Transfer, Charging and Video/Audio enjoyment**

- USB 3.1 data transfer rate up to 10 Gbps, Superspeed+
- Power supply support up to 20V/5A, 100W
- Support of USB PD (Power Delivery) specification
- Support for Video/Audio up to 4K (4096x2304, 30fps)
- Support of DisplayPort Video/Audio signals
- The possible resolution capability depends on the source device

- Device support at DP 1.2: single channel 5.4 Gbps, max resolution: 4K@60Hz
- Device support at DP1.4: single channel, 8.1 Gbps, resolution: 8K@60Hz
- AWG: 30
- Kabel u boji: crni
- Kapice: ukalupljeno
- Konektor 1: USB C, utikač
- Konektor 2: USB C, utikač
- Konektor u boji: crni
- Materijal žice: CU
- Površina konektora: poniklano
- Duljina: 1 m
- oklop: dvostruki oklop
- USB-C proizvodi: Da

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	100	5.90	40.00	30.00	18.00	21.60
Packaging Unit Inside	10	0.59	40.00	35.00	7.60	10.64
Packaging Unit Single	1	0.06	25.00	13.50	1.30	438.75
Net single without Packaging	0	0.05	10.00	10.00	1.30	130.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)