

DIGITUS Prespojni kabel, Kat.6A S/FTP, PUR (TPU)

DK-1644-A-PUR-010
EAN 4016032434696



DK-1644-A-PUR-010 presp. kabel Cat 6A, S/FTP, 1 m PUR, RAL 6018

PUR plašt prespojnih kabela kategorije 6A, S/FTP osigurava otpornost na ulja i UV zračenja. Zbog toga su savršeni za uporabu u industriji. PUR plašt je UV otporan i samogasiv. DIGITUS® prespojni kabeli Kat.6A klase E proizvedeni su i testirani sukladno ISO/IEC 11801 i DIN EN 50173 specifikacijama Kat.6A. Garantiraju sukladnost ugrađenog sustava ožičenja zahtjevima specifikacija ISO & EN kanala i omogućuju optimalne razine performansi DIGITUS® kategorije 6A kabliranja. Performanse su testirane na brzinama do 500 MHz uključujući karakteristike performansi kao što je gubitak preslušavanja na bližem kraju ("NEXT"). Svi prespojni kabeli dizajnirani su i proizvedeni kako bi u potpunosti zadovoljili uporabu u različitim i najzahtjevnijim aplikacijama. Svaki kabel opremljen je s pregibnicom i zaštitom. Pregibnica je opremljena sa zaštitom polugice mikroutikača.

Najbolje performanse i kvaliteta linka Vaše mreže. Idealan za industrijsku primjenu.

- 2x RJ45 (8P8C) mikroutikača
- Pregibnica sa zaštitom
- Oznaka dužine na pregibnici
- Vodič: Bakar (Cu)
- Ambalaža: DIGITUS Polybag
- Asortiman: Patch kabeli s upređenim paricama
- Konfiguracija: 1:1
- Kategorija: CAT 6A
- Oklop: S-FTP, oklop parova u metalnoj foliji i pletenica
- Duljina: 1 m
- Boja: zeleni
- Kapica: PUR
- Struktura: 4 x 2 AWG 26/7, upletena parica
- Tanka verzija: Ne
- Flat Version: Ne

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	180	7.90	46.00	33.00	28.00	42.50
Packaging Unit Inside	10	0.44	5.50	22.00	40.00	4.84
Packaging Unit Single	1	0.04	1.10	14.00	25.00	385.00
Net single without Packaging	0	0.04	100.00	1.17	1.27	148.59

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com