

DIGITUS Universal Docking Station, USB Type-C™

DA-70863
EAN 4016032435396



Universal Docking Station, USB-C, 11 Ports 3x video, 1x USB-C, 3x USB3.0, RJ45, 2x card reader

The fully functional universal docking station, USB Type-C™ from DIGITUS® offers you everything to create a fully equipped workspace. It offers three video interfaces (HDMI, Mini DP, VGA), where two monitors can be operated at the same time. Thus, the best possible supported resolution is achieved: Brilliant UHD (4K2K / 30 Hz). In addition, it offers three USB 3.0 ports, where one port (5 V / 1.5 A) also provides a charging function for mobile devices. The USB interfaces are supplemented by a USB-C™ with power delivery (PD 2.0) functionality. Two card readers are also built in (MicroSD, SDHC, SDXC/MMC). Your notebook can also be connected to your network via cable over the Gigabit Ethernet port. We top everything off with a stereo audio port. Extend your notebook to 11 additional ports using only one USB-C™ port - with the DIGITUS® multifunctional Universal Docking Station USB Type-C™.

Turn your notebook into a fully functional desktop system - extends your notebook with 11 additional ports using only one USB-C™ port.

- Supports Ultra HD (30 Hz), 4096 x 2160p resolution (HDMI, MiniDP)
- Dual monitor function - connect two monitors at the same time (HDMI+MiniDP / VGA+MiniDP)
- 1 x HDMI (UHD resolution, 4K/30 Hz)
- 1 x Mini DisplayPort (UHD resolution, 4K2K, 30 Hz)
- 1 x VGA (Full HD)
- 1 x USB-C™ port with power delivery (PD 2.0) function for fast charging of notebooks (60 W, 20 V / 3 A)
- 3 x USB 3.0 (SuperSpeed, 5 Gbps max.), one port with charging function for mobile devices (5 V/1.5 A)
- 1 x Stereo audio port - connects headphones or microphones
- 1 x Gigabit Ethernet port - connects your notebook to the network via cable
- 2 x Card readers (MicroSD / SDHC, SDXC, MMC)

- USB-C™ version: USB 3.1 (Gen 1)
- Premium and high-quality aluminum housing
- Cable length: 10 cm
- Color: silver
- Dimensions: L 12.0 x W 12.0 x H 1.7 cm
- Weight: 230 g
- Not all USB-C™ ports support all features of the USB Type-C™ standard. Make sure your notebook's USB-C™ port supports DisplayPort Alternate Mode (DP-Alt Mod) and USB Power Delivery (PD).
- The video output capability depends on the graphic card of your notebook and the connected monitor. Certain graphics cards have limited MST support, while some monitors also limit the available resolution.
- The used power supply must supply at least 60 watts to power a connected notebook as well as the docking station via the USB-C™ port
- HDTV Resolution max.: 4096 x 2160 Pixel, 30Hz
- Housing: Aluminum
- LAN connector (RJ45): yes
- USB-C Power Delivery: 60W
- Card reader: yes
- Number of audio ports: 1
- Number of display ports: 2
- Number of network ports: 1
- Number of USB A ports: 3
- Number of USB-C ports: 1
- Number of video ports: 3
- USB-C Products: yes
- Video connection ports: HDMI, DisplayPort, VGA

Package contents

- Universal Docking Station, USB Type-C™
- User manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	15.30	45.00	29.00	39.00	50.90
Packaging Unit Inside	1	0.38	18.00	18.50	2.50	832.50
Packaging Unit Single	1	0.38	18.00	18.50	2.50	832.50
Net single without Packaging	0	0.23	11.90	11.90	1.50	212.42

More images:

