

# DIGITUS Mini DisplayPort Adapter Cable, mDP - HDMI type A

AK-340304-020-W  
EAN 4016032438625



### DisplayPort adapter cable, mini DP - HDMI type A M/M, 2.0m, DP 1.2\_HDMI 2.0, 4K/60Hz,

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with Mini DisplayPort interface to a monitor with HDMI interface.

### Avoid the hassle of adapters, with a plug-and-play adapter cable which doesn't require external power

- Support of HDMI 2.0 Features
- Support up to 4K/2K with 60Hz
- Support of 3D with 1080p resolution
- Support of HDCP and DPCP
- Supported transmission modes: RBR, HBR, HBR2
- Maximal bandwidth: 21,6 Gbps
- HBR-Version/transfer mode: HBR2 (5,40 Gbit/s per lane)
- Ambalaža: Polybag

- Asortiman: DisplayPort kabele
- AWG: 30
- Blokiranje: nema
- DisplayPort standard: DisplayPort 1.2
- HDTV-norma: Ultra HD 4K
- Kabel u boji: bijeli
- Kapice: ukalupljeno
- Konektor 1: Mini DP, utikač
- Konektor 2: HDMI tip A, utikač
- Konektor u boji: bijeli
- Materijal žice: CU
- Površina konektora: poniklano
- Duljina: 2 m
- AOC - aktivni optički kabel: Ne
- oklop: trostruki oklop

### Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	60	4.00	43.00	43.00	25.00	46.23
Packaging Unit Inside	10	0.67	40.00	34.00	10.00	13.60
Packaging Unit Single	1	0.07	16.00	24.00	10.00	3.84
Net single without Packaging	0	0.06	16.00	24.00	4.80	1,843.20

### More images:



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)