

DIGITUS 5 Port Gigabit Ethernet Netzwerk Switch, Industrial, Unmanaged

DN-651107
EAN 4016032454472



Industrial 5-Port Gigabit Switch 5 x 10/100/1000Base-TX Ethernet Ports

The DIGITUS® Industrial Gigabit Switch is designed for harsh environments, where it is exposed to moisture, temperature fluctuations, and vibrations. With a temperature range of -40°C to 85°C, the Industrial Gigabit Switch can be used under the most adverse conditions. It ensures a constant availability in highly sensitive areas such as transport, production, traffic and safety monitoring. The simple plug and play system allows the Industrial Gigabit Switch to be quickly integrated into the respective environment. With its Gigabit connectivity the Industrial Gigabit Switch is a flexible, cost-effective solution for the industrial environment.

Standard / Din Rail mounting dual purpose

- 5 x 10/100/1000Base-TX Ethernet Ports
- Automatic cable detection - Auto MDI / MDI-X function
- Supported standards: IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3ab Gigabit Ethernet
- IEEE802.3x Flow Control und Back Pressure
- Store and forward technology for optimized data transfer
- Automatic speed and half/full duplex recognition/adjustment
- Backplane with 10Gbps
- Supports up to 8K MAC addresses
- Compact, robust metal housing

- Excellent short circuit protection
- Lightning and overvoltage protection
- Suitable for DIN rail (top-hat rail) mounting
- Redundant power supply: 12~56 V DC / 18~36V AC, redundant power supply with reverse polarity protection function
- Extended operating temperature range, -40 °C ~ +85 °C
- Removable terminal connection
- Power supply: 2.76 W
- MTBF: 500,000 hrs.
- EN 50155 (EN 60068-2-6) Vibration
- EN 50155 (EN 60068-2-27) Shock
- EN 50155 (EN 60068-2-32) Free Fall
- Broj priključaka: 5
- Ethernet brzina: Gigabit
- Industrijska uporaba: Da
- PoE (napajanje preko Ethernet): Ne
- Prikladno za vanjsku primjenu: Ne
- Upravljanje: Ne
- VLAN: Ne
- Vrsta instalacije: DIN tračnica
- Zaštita od vandalizma: Ne

Package contents

- Industrial 5-Port Gigabit Switch
- Quick start guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	16	7.40	35.00	24.00	56.00	47.04
Packaging Unit Inside	16	7.40	35.00	24.00	56.00	47.04
Packaging Unit Single	1	0.46	16.50	6.50	21.50	2,305.88
Net single without Packaging	0	0.16	8.15	3.20	10.35	269.93