

DIGITUS USB-C™ 3in1 Triple Monitor Adapter (HDMI, DP, VGA)

DA-70859

EAN 4016032456476



USB-C Graphics Adapter, triple display Display Port/HDMI/VGA Adapter

This multi-graphics adapter supports the output of up to 3 equal or different video signals to 3 different output displays - HDMI, DisplayPort and VGA. Obviously, it is also possible to operate only one monitor. The HDMI connection supports UHD resolutions up to 4K/30 Hz, the DP connection up to 4K/60 Hz (single monitor). Plug & Play - plug in and get started. Ideal for field workers who come upon different connections in meeting rooms, or for the private user who wants to output content to various output devices such as a TV set, video projector, etc. at home. The compact dimensions are ideal for mobile use.

3 additional graphic interfaces on your laptop (HDMI, DP and VGA) - simultaneous operation of up to 3 monitors

- Play the same or different content on 3 ports
- HDMI resolution: Max. UHD 4K/30 Hz
- DisplayPort resolution: Max. UHD 4K/60 Hz
- VGA resolution: Max. Full HD 1920 x 1200/60 Hz
- Plug & Play installation - no additional software required

- Supports DP++
- Triple display support under Windows OS - SST (single stream transport) and MST (multi stream transport) - mirror and extend the monitor
- Triple display support under Mac OS - SST (Single Stream Transport) - mirror the monitor
- The output device resolution depends on the number and type of connected devices and the operating system
- Cable length: 11.0 cm
- Power supply: USB-C™ port of the notebook
- Operation temperature: 0°C to +45°C
- Dimensions: L 8.4 x W 4.2 x H 1.4 cm
- Weight: 43 g
- Color: White

Attributes

- USB-C Products: yes

Package contents

- USB-C™ 3in1 Triple Monitor Converter (HDMI, DP, VGA)
- QIG (quick installation guide)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	12.30	28.00	57.00	23.00	36.71
Packaging Unit Inside	10	3.08	21.00	27.50	13.00	7,507.50
Packaging Unit Single	1	0.31	11.50	16.00	2.50	460.00
Net single without Packaging	0	0.04	4.20	8.80	1.50	55.44

More images:



Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com