

# DIGITUS Industrial 8 Port Gigabit PoE Switch, Unmanaged, 2 Uplinks

DN-651110  
EAN 4016032457930



### Industrial Gigabit Ethernet PoE+ Switch 8-port PoE + 2-port SFP, 802.3at, DIN rail

The DIGITUS® industrial Gigabit PoE switch is intended for harsh environments where it is exposed to moisture, temperature fluctuations, and vibrations. With a temperature range of -40 °C to 75 °C, the industrial Gigabit PoE switch can be used under the most adverse conditions. The PoE capable devices can be powered via the PoE ports with IEEE802.3af/at support with up to 30 W per port. A constant availability in the highly sensitive areas such as transport, production, traffic and security surveillance is ensured. The simple plug-and-play system allows a fast integration of the industrial Gigabit PoE switch into the respective environment. With Gigabit connectivity and SFP uplink ports, the industrial Gigabit PoE switch provides a flexible, cost-effective solution for the industrial environment.

### Rugged and durable industrial solutions with integrated Power over Ethernet (PoE) function

- 8x 10/100/1000Base-TX Ethernet PoE ports
- 2x 1000Base-X SFP uplink ports
- Supports IEEE802.3af/at
- Supported standards: IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3z Gigabit Ethernet
- Backplane 20G
- MAC address memory 4K

- Compact, sturdy metal enclosure
- Excellent short-circuit protection
- Lightning protection and overvoltage protection
- Suitable for DIN rail (top-hat rail) mounting
- Redundant power supply: 48-57 V/DC, redundant power supply with polarity reversal protection function
- Extended operating temperature range, -40 °C ~ +75 °C
- Removable terminal connection
- Number of ports: 8
- PoE Power budget: 30 W
- PoE standard: IEEE802.3at (PoE+)
- Ethernet speed: Gigabit
- Industrial usage: yes
- Installation type: DIN rail
- Managed: no
- Number of ports (Uplink): 2
- Outdoorsuitable: no
- PoE (Power over Ethernet): yes
- Protection against vandalism: no
- Uplink port connection: SFP
- VLAN: no

### Package contents

- Industrial 8-port Gigabit PoE switch with 2x SFP uplink ports
- Quick start guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	10	11.18	25.50	45.50	41.00	47,570.20
Packaging Unit Inside	1	1.12	18.60	23.10	8.40	3,609.14
Packaging Unit Single	1	1.12	18.60	23.10	8.40	3,609.14
Net single without Packaging	0	0.93	14.70	16.50	5.40	1,309.77

More images:

