

# DIGITUS Industrial 8 Port Gigabit PoE Switch, Unmanaged, 2 Uplinks

DN-651110  
EAN 4016032457930



### Industrial 8-port Gigabit PoE+Switch w. 2x SFP upl IEEE802.3af/at, DIN rail, extended temp. range

The DIGITUS® industrial Gigabit PoE switch is intended for harsh environments where it is exposed to moisture, temperature fluctuations, and vibrations. With a temperature range of -40 °C to 75 °C, the industrial Gigabit PoE switch can be used under the most adverse conditions. The PoE capable devices can be powered via the PoE ports with IEEE802.3af/at support with up to 30 W per port. A constant availability in the highly sensitive areas such as transport, production, traffic and security surveillance is ensured. The simple plug-and-play system allows a fast integration of the industrial Gigabit PoE switch into the respective environment. With Gigabit connectivity and SFP uplink ports, the industrial Gigabit PoE switch provides a flexible, cost-effective solution for the industrial environment.

### Rugged and durable industrial solutions with integrated Power over Ethernet (PoE) function

- Automatic cable detection - Auto MDI / MDI-X function

- Broj priključaka: 8
- PoE norma: IEEE802.3at (PoE+)
- PoE potrošnja energije: 30 W
- Ethernet brzina: Gigabit
- Industrijska uporaba: Da
- Broj priključaka (Uplink): 2
- PoE (napajanje preko Etherneta): Da
- Prikladno za vanjsku primjenu: Ne
- Upravljanje: Ne
- Veza uzlaznog (Uplink) priključka: SFP
- VLAN: Ne
- Vrsta instalacije: DIN tračnica
- Zaštita od vandalizma: Ne

### Package contents

- Industrial 8-port Gigabit PoE switch with 2x SFP uplink ports
- Quick start guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	10	11.18	25.50	45.50	41.00	47,570.20
Packaging Unit Inside	1	1.12	18.60	23.10	8.40	3,609.14
Packaging Unit Single	1	1.12	18.60	23.10	8.40	3,609.14
Net single without Packaging	0	0.93	14.70	16.50	5.40	1,309.77

More images:

