

DIGITUS Mini enclosure for M.2 NVMe PCIe SSD, USB 3.1 Type-C™

DA-71120
EAN 4016032461432



USB Type-C 3.1 External SSD Enclosure M.2 (NVMe) tool-free, alu housing, M-Key or B+M-Key

The external Mini SSD enclosure from DIGITUS® enables installation of your SSD in M.2 NVMe PCIe format in a modern aluminium enclosure. You can easily insert the storage medium into the enclosure and secure it with the supplied screw. You can then connect it directly to your PC or laptop using the supplied USB-C™ combo cable. The combo cable allows you to connect devices using both USB-C™ and USB-A ports. Thanks to plug-and-play, you can access your data anywhere and any time and enjoy data transfer rates of up to 10 Gbps with the USB 3.1 standard. The slim and stylish aluminium enclosure enables comfortable transfer and retrieval of your data at all times. No additional power adaptor is required, power is supplied via the USB Type-C™ port.

The external Mini SSD enclosure accommodates an M.2 NVMe PCIe SSD, and USB 3.1 Type-C™ provides data transfer rates of up to 10 Gbps.

- Supports Mini SSD in M.2 NVMe PCIe format
- Supported capacity: up to 2 TB
- Easy installation, insert storage medium and secure with screws.
- USB 3.1 (Gen. 2) SuperSpeed - data transfer rate up to 10 Gbps
- Supports M.2 modules in 2280, 2260, 2242, and 2230 formats with M or B+M Key (PCIe (NVMe))

- Backwards compatible with USB: 3.0 / 2.0 / 1.1
- Chipset: JMS583
- LED activity indicator
- Stylish and high-quality aluminium enclosure
- Supports plug-and-play
- Power is supplied via the USB port
- Supports: Win 10, 8, 7, XP, 2000, macOS 9.x or higher, Linux 2.4.x or higher, Google Chrome OS
- Operation temperature: 5 to 50 °C
- Storage temperature: -40 to 70 °C
- Operating humidity: 5 to 90% (non-condensing)
- Dimensions: L 112 x W 40 x H 12 mm
- Weight: 306 g
- Colour: Black
- USB-C proizvodi: Da

Package contents

- Mini enclosure for M.2 NVMe PCIe SSD, USB 3.1 Type-C™
- USB 3.1 SuperSpeed cable Type-C™ to USB-A plug
- USB Type-C™ adapter to USB-A socket
- User Manual
- Mounting accessories

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	40	8.00	53.50	32.50	20.50	35,644.40
Packaging Unit Inside	1	0.20	15.00	9.00	5.00	675.00
Packaging Unit Single	1	0.20	11.20	4.00	1.20	53.76
Net single without Packaging	0	0.06	11.20	4.00	1.20	53.76

More images:



Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com