


DIGITUS Prespojni kabel, Kat.6A S/FTP, testiran na razini svake komponente

DK-1644-A-030CL
EAN 4016032464679



CAT 6A S/FTP patch cord, Cu, LSZH AWG 26, length 3 m, color grey

DIGITUS® prespojni kabeli Kat. 6A klase EA proizvedeni su i testirani sukladno ISO/IEC 11801 i DIN EN 50173 Kat.6A specifikacijama. Garantiraju sukladnost ugrađenog sustava ožičenja zahtjevima specifikacija ISO & EN kanala i omogućuju optimalne razine performansi DIGITUS® kategorije 6A kabliranja. Kabeli su testirani na razini komponente, tj. komponente kabela se pojedinačno testiraju. Performanse su testirane na brzinama do 500 MHz uključujući karakteristike performansi kao što je gubitak preslušavanja na bližem kraju ("NEXT"). DIGITUS® prespojni kabeli dizajnirani su i proizvedeni kako bi u potpunosti zadovoljili uporabu u različitim i najzahtjevnijim aplikacijama. Svaki kabel opremljen je s pregibnicom i zaštitom. Pregibnica je opremljena sa zaštitom polugice mikroutikača. Kategoriju 6A možete vrlo jednostavno prepoznati po mikroutikaču prozirno žute boje.

Vrhunsku kvalitetu Vaše mreže osigurava oprema proizvedena sukladno najnovijim standardima - testirana na razini komponente




- 2x RJ45 (8P8C) mikroutikača
- Pregibnica sa zaštitom
- Oznaka dužine na pregibnici
- Vodič: Cu

Attributes

- Konfiguracija: 1:1
- Kategorija: CAT 6A
- Oklop: S-FTP, oklop parova u metalnoj foliji i pletenica
- Duljina: 3 m
- Boja: sivi
- Kapica: LSOH
- Struktura: 4 x 2 AWG 26/7, upletena parica
- Tank verzija: Ne
- Flat Version: Ne

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	80	9.60	46.00	33.00	28.00	42.50
Packaging Unit Inside	1	0.12	30.00	36.00	10.00	10.80
Packaging Unit Single	1	0.12	1.80	17.00	25.00	765.00
Net single without Packaging	0	0.10	300.00	1.17	1.27	445.77

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com