

DIGITUS 11-Port USB-C™ Docking Station with SSD Enclosure (M.2)

DA-70889

EAN 4016032465010



11 Port USB-C Dock with SSD Enclosure 2x HDMI, DP, 4x USB-A, 2x USB-C, RJ45, AC, M.2 SSD

This DIGITUS® 11-in-1 docking station provides you with a housing for M.2 NGFF SSD memory in addition to the common interfaces such as HDMI®, DisplayPort™, USB or Ethernet. Here you can buffer or store data, e.g. for a presentation. Extend your system by 3 additional displays with resolutions of up to UHD 4K; e.g. connect your monitor, projector or TV devices. 2 USB-C™ ports enable you to connect your notebook with a power adapter. This allows you to charge your notebook via Power Delivery. Use the third USB-C™ port to connect additional USB-C™ devices with SuperSpeed (5 Gbps). 4 x USB 3.0 ports give you plenty of connectivity options for peripheral devices: Connect your keyboard, mouse, printer USB sticks or external hard drives. A Gigabit Ethernet is integrated as well. This allows you to connect to the Internet and also provides you with an audio connection for earphones, speakers or headsets. Utilize of the full USB-C™ potential and trust in the DIGITUS® 11-in-1 docking station as well as its M.2 NGFF memory installation option.

All-round docking station with housing for M.2 NGFF SSDs and 3 graphic interfaces - a total of 11 additional connections for notebooks & tablets

- 1 x M.2 SATA 3.0 NGFF SSD housing (5 Gbps) - suitable for B-Key or B+M key (PCIe-based)
- Supported SSD sizes: 80 mm (2280), 60 mm (2260), 42 mm (2242) and 30 mm (2230)
- Supported SSD capacity: 2 TB max.
- 1 x HDMI® connection: 4K / 30 Hz (3840 x 2160p)
- 1 x HDMI® connection: 4K / 60 Hz (3840 x 2160p / source DP1.4 = 60 Hz, DP1.2 = 30 Hz)
- 1 x DisplayPort™: 4K / 60 Hz (3840 x 2160p)
- 1 x USB-C™ host connection: SuperSpeed, 5 Gbps
- 1 x USB-C™ connection: SuperSpeed, 5 Gbps, 15 W (5 V / 3 A)
- 1 x USB-C™ Power Delivery 3.0 (100 W max.)
- 2 x USB A connection: SuperSpeed, 5 Gbps (USB 3.0), 7.5 W (5 V / 1.5 A)
- 2 x USB A connection: SuperSpeed, 5 Gbps (USB 3.0), 4.5 W (5 V / 0.9 A)

- 1 x Gigabit Ethernet connection: RJ45, 10/100/1000 Mbps
- 1x power supply: DC socket: 36 W (12 V / 3 A) for additional power supply for the docking station (not PD)
- USB-C™ version: USB 3.1 Gen 1
- LED feature display
- Supported operating systems: Windows 10/8/7, macOS® X 10.6 or higher, iOS, Android 6.0 or higher, Google Chrome OS, Linux 2.6.14 or higher
- Color: Black
- Dimensions: W 12 x D 7 x H 6.1 cm
- Weight: 322g (without charger) / 520 g (incl. charger)
- Manufacturer's notice:
- Not all USB-C™ ports support all functions of the USB Type-C™ standard. Make sure that your notebook's USB-C™ port supports the DisplayPort Alternate Mode (DP Alt Mode) as well as USB Power Delivery (PD).
- Source device must support DisplayPort™ V1.4 in order to output 4K / 60 Hz video.
- HDTV Resolution max.: 3840 x 2160 Pixel, 60Hz
- Housing: Aluminum
- LAN connector (RJ45): yes
- USB-C Power Delivery: 100W
- Card reader: no
- Number of audio ports: 1
- Number of display ports: 3
- Number of network ports: 1
- Number of USB A ports: 4
- Number of USB-C ports: 2
- Number of video ports: 3
- USB-C Products: yes
- Video connection ports: HDMI, DisplayPort

Package contents

- USB-C™ Triple Display Docking Station M.2 NGFF SSD
- Power supply 12 V / 3 A
- USB-C™ - USB-C™ connection cable
- Screw set
- User manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	15	9.40	40.80	72.00	22.00	64,627.20
Packaging Unit Inside	1	0.63	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.63	12.40	18.40	13.40	3,057.34
Net single without Packaging	0	0.56	7.00	12.00	68.00	5.71

More images:



Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.

- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com