

DIGITUS Outdoor 1 to 2 port UPoE Extender, IEEE803.2af/at 2 Port

DN-95126-1
EAN 4016032479710



Outdoor 1 to 2 UPoE Extender IEEE803.2af/at 1 port in 95W, 2 ports out supports 75W/30W/15,4W

DN-95126-1 is a Gigabit IP67 waterproof PoE extender. It Supports one RJ45 (PD) port with IEEE802.3bt Standard up to 95W. Two Ports has PSE function, each supporting up to 30 W PoE output, without configuration, easy plug and play installation.

Complies with IEEE802.3af/at/bt Standard

- Supported Standards: IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3x, IEEE802.3af, IEEE802.3at, IEEE802.3bt
- Ports: 1 x PoE in (up to 95 W), 2x PoE out (10/100/1000 Mb/s)
- PoE Standard: IEEE802.3af/at/bt
- Dimensions(L*W*H): 150,73,44 mm

- PoE IN Port: Anode 1/2, Cathode 3/6 or Anode 4/5, Cathode 7/8
- Number of PoE Ports: 2
- Power Supply: PoE
- PD port input 95W max
- PoE Power Output: Per Poert 48-55V DC , max. 30W
- operating Temperature: -20°C to 60°C
- Storage Temperature: -40°C to 80°C
- Surge Protection: Differential mode +/- 4KV, Common mode +/- 6KV
- IP Rating: IP67
- Vandal Proof: IK10
- Industrial usage: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	8.47	26.40	45.00	39.00	46.33
Packaging Unit Inside	1	0.85	18.60	24.00	8.40	3,749.76
Packaging Unit Single	1	0.85	18.60	24.00	7.87	3,513.17
Net single without Packaging	0	0.48	7.30	15.00	4.75	520.13

More images:



