

DIGITUS Socket Strip with Aluminum Profile, 9-way, IEC C20 input

DN-95430
EAN 4016032483564



1U Aluminum PDU, rackmountable, 7 x C13, 2 x C19 16A, 230VAC, 50/60Hz, IEC C20 inlet

The DIGITUS® socket strips are the perfect solution for your network or server cabinet. With regard to current distribution, the PDU fulfills the requirements of many applications in IT, network technology and laboratories. The PDU can be used ideally with your input connector IEC60320 C13 and C19 as additional 19" distribution for UPS.

Safe and professional current supply in the 19" range

- Horizontal 19" installation in the rack
- Housing: Aluminum profile
- Plastic components made of ABS UL-94V-0
- Input: IEC60320 C20, 230 Vac / 16 A
- Output: Device sockets 7 x IEC60320 C13, 2 x IEC60320 C19

- Dimensions: 482.6 (19") x 45 (1U) x 45 mm (HxWxD)
- Current: 16 A
- Input Plug: IEC 60320 C20 inlet
- Installation: Rack 1U
- Outlets: IEC 60320 C13, IEC 60320 C19
- Phase: 1ph
- Power: 3,6 kVA
- Volts: 230 V
- Inch form factor (IEC 60297): 482.6 mm (19")

Package contents

- Scope of delivery: 1 socket strip, 2 mounting brackets; 1 safety instructions

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	10	8.92	19.50	52.00	29.50	29.91
Packaging Unit Inside	1	0.89	5.80	9.70	51.00	2,869.26
Packaging Unit Single	1	0.89	9.70	51.00	5.80	2,869.26
Net single without Packaging	0	0.65	4.50	48.26	4.46	968.58

More images:



