


DIGITUS Cat.7A S/FTP, installation cable, 100 m, duplex, Dca-s1a d1 a1

DK-1743-A-VH-D-1
EAN 4016032483632



CAT 7 S-FTP installation cable, 1200 MHz Dca (EN 50575), AWG 23/1, 100 m ring, DX, orange

The Digitus Cat 7 installation cable is designed for use in the structured data center and the building cabling according to ISO/IEC 11801, DIN EN 50288-4-1, DIN EN 50173, IEC 61156-7, EN 50288-9-1. The cable is perfectly suitable for the transmission of both analog and digital data and also supports POE and POE+. The shielding structure is composed of single shielded pairs with a tinned copper braid, which ensures excellent shielding and electrical values.

Future-oriented standards and high-end quality for your network.


- Physical properties:
- Basic conductor: Solid AWG 22/1, bare annealed copper, diameter 0.62 mm nominal
- System/s of AVCP: AVCP 3
- Insulation: SFS-PE (Foam-Skin Polyethylene)
- Total number of insulated conductors: 8, twisted in 4 pairs
- Color code: blue-white, orange-white, green-white, brown-white
- Individual pair shielding: Aluminum foil, providing 100 % coverage
- Overall shielding: Copper wire braid
- Outer jacket: Halogen-free (FRNC-C/LSZH-3)
- Outer jacket diameter: 0.6 mm nominal
- Color: Yellow (RAL 1016)
- Length: 100 m
- Mechanical properties:

- Tensile loading: 150N max.
- Dynamic bending radius: 8x AD mm min.
- Static bending radius: 4x AD mm min.
- Shipping- and storage temperature range: -20 °C up to +60 °C
- Operating temperature range: -20 °C up to +60 °C
- Temperature installation range: 0°C to +50°C
- Overall diameter: 8.0 mm nominal
- Flame retardancy: IEC 60332-3-24
- Halogen-free & smoke-proof: IEC 60754-2 & IEC 61034
- Fire load: 700 MJ/km
- Electrical properties:
- Mean impedance: 100±5 Ohm @ 1-600 MHz
- Capacitance: 40 pF/m nominal @ 1 KHz
- Capacitance unbalance (pair-ground): 1.6 pF/m max. @ 1 KHz
- Insulation resistance: 5 GOhm x km min.
- DC loop resistance: 147 Ohm/Km max. (2% max. resistance unbalance)
- Voltage resistance: 72 Vdc max.
- Coupling attenuation: Grade 1 (CA-Type 1b)
- Propagation delay: 10 nS/100 m max.
- Signal propagation delay: 450 nS/100 m max.
- Separating class: "d" acc. to EN 50174-2
- NVP: 75%
- Flame spread: EN 60332-1-2 (LSOH-PVC)
- Halogen-free, corrosiveness: EN 60754-1/2 (LSOH)
- Smoke density: EN 61034-2

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	10.14	36.00	36.00	16.00	20.74
Packaging Unit Inside	1	10.14	0.00	0.00	0.00	0.00
Packaging Unit Single	1	10.14	36.00	36.00	16.00	20.74
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

DIE LEHRPLÄNE		DIGITALE LEHRPLÄNE	
1998 Lehrplan Kommunikation	2002 Lehrplan Kommunikation	2006 Lehrplan Kommunikation	2014 Lehrplan Kommunikation
B2+ Sachliche Kommunikation	1+ Sachliche Kommunikation	1+ Sachliche Kommunikation	1+ Sachliche Kommunikation
C1+ Hoch sprachliche Kommunikation	2+ Hochsprachliche Kommunikation	2+ Hochsprachliche Kommunikation	2+ Hochsprachliche Kommunikation
D1+ Hoch sprachliche Kommunikation	3+ Hochsprachliche Kommunikation	3+ Hochsprachliche Kommunikation	3+ Hochsprachliche Kommunikation
E1+ Geringste Kommunikation	4+ Geringste Kommunikation	4+ Geringste Kommunikation	4+ Geringste Kommunikation



Leistungsgemeinschaften Transmitter Properties									
Trans	APT	RGPT	PR NGPT	ACH	PR ACH	SL	SLVPT	PR SLVPT	
Min	40	40	Min	Min	40	40	40	40	
1	15	15	15	15	15	15	15	15	15
2	25	15	15	15	15	15	15	15	15
3	14	14	15	15	15	15	15	15	15
10	14	14	15	15	15	15	15	15	15
20	14	14	15	15	15	15	15	15	15
30	14	14	15	15	15	15	15	15	15
40	14	14	15	15	15	15	15	15	15
50	14	14	15	15	15	15	15	15	15
60	14	14	15	15	15	15	15	15	15
70	14	14	15	15	15	15	15	15	15
80	14	14	15	15	15	15	15	15	15
90	14	14	15	15	15	15	15	15	15
100	14	14	15	15	15	15	15	15	15

[illegible]