

DIGITUS Pre-assembled Fiberglass Universal Breakout Cable, Multi Mode OM4, 12 Fibers, LC/UPC - LC/UPC

DK-2433CUE50BK-BBB
EAN 4016032484318



Breakout cable 12 Fibers, OM4, LC/UPC-LC/UPC universal, color black, 150m

This pre-assembled breakout fiberglass cable is perfect for installations that require an extremely robust and reliable fiberglass design where maximum mechanical protection is necessary. It offers a secure Plug & Play solution for installations with the pre-assembled plug. Easy installation on partially equipped patch panels, for example. The measurement report included in delivery eliminates the need for laborious follow-up inspection.

Pre-assembled fiberglass breakout cables enable easy, time-saving and flexible installation of network routes with a high bandwidth.

- Cable type: Breakout / Universal cable (I/A-DQ (ZN) BH X G 50/125µm)
- Fiber category: Multi mode
- Fiber type: OM4 50/125
- Number of strands: 12
- Length: 150
- Plug connection 1: LC/UPC
- Plug connection 2: LC/UPC
- Sheath material: Dca
- Color of outer sheath: Black

- Halogen-free (in accordance with EN 50267-2-3): Yes
- IL in multi mode: max. 0.3 dB
- IL in single mode: max. 0.3 dB
- RL in multi mode: min. 30 dB
- RL in single mode: min. 50 dB
- Operating temperature: -20 to 70°
- Storage temperature: -20 to 70°
- Two-sided insertion tool
- Application: universal
- Boot: single-color
- Cable jacket: LSOH
- Cable type: U-DQ (ZN) BH X G 50/125µm
- Color cable: black
- Connector 1: LC
- Connector 2: LC
- Fiber class: OM4
- Fiber diameter: 50/125µ
- Mode: Multimode
- Number of connectors side 1: 1
- Number of connectors side 2: 1
- Number of fibers: 12
- Polishing: UPC
- Length: 150 m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	6.40	46.00	46.00	28.00	59.25
Packaging Unit Inside	1	6.40	0.00	0.00	0.00	0.00
Packaging Unit Single	1	6.40	0.00	0.00	0.00	0.00
Net single without Packaging	0	6.40	42.00	42.00	15.00	26.46

More images:

