

DIGITUS Pre-assembled Fiberglass Universal Breakout Cable, Single Mode OS2, 12 Fibers, LC/UPC - LC/UPC

DK-2A33CU030BK-BBB
EAN 4016032485100



Breakout Kabel 12 Fasern, SM G.657.A1, LC/UPC-LC/UPC, universal, Farbe: schwarz, 30m

This pre-assembled breakout fiberglass cable is perfect for installations that require an extremely robust and reliable fiberglass design where maximum mechanical protection is necessary. It offers a secure Plug & Play solution for installations with the pre-assembled plug. Easy installation on partially equipped patch panels, for example. The measurement report included in delivery eliminates the need for laborious follow-up inspection.

Pre-assembled fiberglass breakout cables enable easy, time-saving and flexible installation of network routes with a high bandwidth.

- Cable type: Breakout / Universal cable (I/A-DQ (ZN) BH X E 9/125µm)
- Fiber category: Single mode
- Fiber type: OS2 G.657.A1 9/125
- Number of strands: 12
- Length: 30
- Plug connection 1: LC/UPC
- Plug connection 2: LC/UPC
- Sheath material: Dca
- Color of outer sheath: Black

- Halogen-free (in accordance with EN 50267-2-3): Yes
- IL in multi mode: max. 0.3 dB
- IL in single mode: max. 0.3 dB
- RL in multi mode: min. 30 dB
- RL in single mode: min. 50 dB
- Operating temperature: -20 to 70°
- Storage temperature: -20 to 70°
- Two-sided insertion tool
- Broj konektora strane 1: 1
- Broj konektora strane 2: 1
- Broj vlakana: 12
- Kabel u boji: crni
- Kabelski omotač: LSOH
- Klasa vlakna: OS2
- Konektor 1: LC
- Konektor 2: LC
- Mod: Jednomodni
- Poliranje: UPC
- Primjena: univerzalna
- Promjer vlakna: 9/125µ
- Stopica: jednobojna
- Vrsta kabela: U-DQ (ZN) BH X E 9/125µm
- Duljina: 30 m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	4	8.00	46.00	46.00	28.00	59.25
Packaging Unit Inside	1	2.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	2.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	2.00	42.00	42.00	5.00	8.82

More images:

