

DIGITUS 16-Port Fast Ethernet PoE Networkswitch, 19 Zoll, unmanaged, 2 Uplink Ports, SFP, 250 W, af/at

DN-95342-1
 EAN 4016032485667



Fast Ethernet PoE Switch 16-port PoE + 2 Combo, 250W PoE budget

The DIGITUS® Fast Ethernet PoE switches are designed for medium to large network systems. The PoE function and the 19" size enable an uncomplicated integration into your network. The switches are a great choice to improve the performance and efficiency of your network.

Integrated Power over Ethernet (PoE) for small and medium network environments

- 16-port 10/100Base-TX with PoE support
- 2-Port Combo Gigabit TP/SFP Uplink
- Complies with the network standards IEEE 802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.3af, IEEE802.3at
- PoE power output 55V DC voltage, max. 30 W per port
- PoE power supply mode A, PIN 1/2(+), 3/6(-) Supports non-blocking, non-head-of-line forwarding Store-and-forward technology for optimized data transfer
- Automatic speed and half/full duplex detection/adjustment
- Auto MDI/MDI-X function
- 8K MAC addresses
- Integrated power supply unit

- Power consumption: 270 watts
- Maximum PoE output power: 250 watts
- Power supply: AC:100-240V
- Power consumption: 4.34W

Attributes

- Number of ports: 16
- Ethernet speed: Fast Ethernet
- Industrial usage: no
- Managed: no
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vandalism: no
- VLAN: yes

Package contents

- 16-port Fast Ethernet PoE Switch
- Quick start guide
- Power Cable
- Mounting accessories

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	3	10.83	26.50	49.30	31.00	40,499.90
Packaging Unit Inside	1	3.61	0.00	0.00	0.00	0.00
Packaging Unit Single	1	3.61	29.00	48.00	8.30	11,553.60
Net single without Packaging	0	2.74	21.00	44.00	4.40	4,065.60

<https://www.assmann.com>
info@assmann.com