

DIGITUS 8- Port Fast Ethernet PoE Networkswitch, Desktop, unmanaged, 60 W, af/at

DN-95354
EAN 4016032485919



8+2 Port FE PoE Switch 8 Port PoE 802.3af, 10/100 Mbps

DN-95354 has a CCTV function which can improve the network environment and reduce network maintenance costs. It's easy to manage and meet the networking and access requirements of Business buildings, community, hotel and office.

The electrical power and data transmission on the same cable can expand your network easy to the places where no power line available.

- Interface: 10* 10/100 RJ45 port
- PoE standard: IEEE802.3af/at
- PoE port: 1~8
- PoE total: 60W
- Power supply: 65W
- Key function: CCTV
- PoE port output: Max 30W
- RJ45 PoE power supply: Mode A Anode1/2 Cathode3/6
- Indicator: PWR (Green), LNK/ACT (Green), PoE (Orange), Max (Green)
- Network media: 10BASE-T: UTP category 3,4,5 cable $\leq 100m$
- 100BASE-TX: UTP category 5, 5e cable $\leq 100m$
- MAC Address Table: 1K, Automatic study, automatic updates

- Jumbo frame: 1536 Bytes
- Packet buffer: 448Kbit
- Transfer Mode: Store-and-forward
- Packet Forward Speed: 14.88Mpps
- Bandwidth: 2 Gbps
- Device Dimension: 168*93*32mm
- green energy saving: Support IEEE802.3az
- mains input: 100~240V AC, 50/60Hz
- Operating Temperature: 0°C ~ 40 °C
- Storage Temperature: -40 °C ~ 70 °C
- Operating Humidity: 10% ~ 90% non-condensing
- Storage Humidity: 5% ~ 90% non-condensing
- Surge Protection: Common mode $\pm 6KV$, differential mode $\pm 2KV$
- MTBF: >50000 hour
- Electrostatic standard: Contact 6KV, air 8KV
- Industrial usage: no

Package contents

- PoE Switch
- User Guide
- Power Cord

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	15.10	35.30	32.00	40.30	45,522.90
Packaging Unit Inside	1	0.76	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.76	6.00	16.50	19.20	1,900.80
Net single without Packaging	0	0.45	3.20	9.40	16.80	505.34

More images:

