

DIGITUS Basic IT PDU, 1-phase 16A, 24 x C13, 3 x C19, 3 m supply cable, IEC 60309 16 A plug

DN-95450
EAN 4016032485957



IT BASIC PDU, Vertical, 16A, 24 x C13, 3 x C19 1-phase, 3m cable, IEC309 16A plug

The DIGITUS® PDU are the perfect solution for your network or server cabinet. With regard to power distribution, it fulfills the requirements of many applications in IT, network technology and laboratories. The individual C13 and C19 outlets are equipped with extract protection. It is optimally designed for vertical installation providing the advantage of saving rack spaces for more equipments. The 27 outlet PDU has excellent physical characteristics and is engineered for an output of up to 4,000 W (250 V AC / 16 A) which helps in achieving best performances with the appropriate load.

Safe and professional power distribution solution for highly demanding IT requirements in network and server racks

- Extraction protection at each output (for C13 and C19 standard cables)
- Vertical installation
- Housing: Aluminum

- Plastic components made of ABS UL-94V-0
- Mains plug: 2.5 mm², IEC60309 16 A plug
- Cable: 3 m
- Max. Load: 4000 W / 250 V AC / 16 A (50/60Hz)
- Outlets: 24 x IEC60320 C13, 3 x IEC60320 C19
- Output power: C13 (10A), C19 (16A)
- Dimensions (L x W x D): 1140,5 x 45 x 60 mm
- Colour: Black
- El. snaga: 3,6 kVA
- Faze: 1 fazni
- Izlazni priključci: IEC 60320 C13, IEC 60320 C19
- Struja: 16 A
- Ugrađivanje: Stalak 0U
- Ulazni utikač: IEC 60309 16A 1ph/N/PE 6h
- Volti: 230 V

Package contents

- Scope of delivery: 1 socket strip, 1 safety instructions

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:

