

# DIGITUS SC/UPC Fiber Optic Fast connector (10 Pieces)

DN-FC-9100  
EAN 4016032486800



### SC Fast Connector UPC

The SC/UPC fast connectors are used to close optical cables and fast cross-connection, cable repair, various switching nodes in FTTH networks to form a continuous optical patch. They completely eliminate the need for hand polishing in the field. The mechanical splice technology ensures precise fiber alignment and offers an immediate low loss termination for single-mode optical fibers. The attenuation obtained does not exceed 0.3 dB. The connectors can be used in all optical networks where UPC type connector is required. It is suitable for optical cabling in primary/secondary/tertiary cabling and for use in FTTH networks.

**Fast connectors are designed to enable quick and easy termination of fibers in the field. For uncomplicated fast repair of existing installations as well as for new installations, e.g. for FttX in-house cabling.**

- Connector Type : SC
- Polishing : UPC
- Fiber Mode : 9/125µm Singlemode
- Ferrule : Ceramic (2,5mm)
- Insertion Loss ≤0.2dB
- Return Loss ≥50dB
- Cable Diameters : 0.9/2.0/3.0mm
- Product colour : Black, Blue
- Storage Temperature : -40 to 85°C
- Operating Temperature : -20 to 75°C
- Dimension : 55mm long

### Package contents

- 10 x SC/UPC Fiber Optic Connector

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	2	10.10	26.00	32.00	46.00	38.27
Packaging Unit Inside	100	0.51	7.80	12.00	15.00	1.40
Packaging Unit Single	10	0.05	1.50	7.10	14.50	154.43
Net single without Packaging	0	0.00	56.50	1.00	1.00	56.50

### More images:



