

# DIGITUS Label Printer 300dpi

DA-81021  
EAN 4016032487036



**Bar Code Label Printer, 300dpi Thermal Direct/Transfer, USB, LAN, Serial**

The DIGITUS Label Printer is a high quality thermal printer for individual and business label printing that fits comfortably on the desktop. The printer offers a resolution of 300 DPI, a print speed of up to 101mm/s and a USB 2.0/RS-232/Ethernet interface. The printer is ideal for product labeling, shipping labels, retail and other labeling applications. The label roll is located directly in the housing.

**The label printer is versatile and ideal for creating shipping labels and barcode labels in the office and at home**

- Resolution 300 DPI
- Printing method thermal transfer / direct thermal
- Max. Print speed: 101,6mm (4")/s Max.
- Max. Print width/length: 104mm (4.09") /1016mm (40")
- Print media: continuous, gap, black mark, fanfold and perforation
- Media width/thickness: 25.4-118mm (1.0-4.6") / 0.06-0.254mm (2.36-10mil)
- Media core diameter 25.4-76.2mm (1-3")
- length of label: 10-1016mm 0.39-40"
- Label roll capacity 127mm (5") (outer diameter).
- Ribbon capacity Max: 300m
- Ribbon width: 110mm
- Ribbon core inner diameter: 25.4mm (1")
- Performance Features: Processor 32-bit CPU

- Memory 4MB flash memory, 8MB SDRAM, SD card reader for flash memory expansion, up to 4GB
- Interface: USB2.0/Serial/Ethernet
- Internal fonts: 8 alphanumeric bitmap fonts, Windows fonts can be downloaded from software
- 1D barcode: Code 39, Code 93, Code 128UCC, Code 128, subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11
- 2D barcode PDF-417, Maxicode, DataMatrix, QR code, Aztec
- Rotation: 0°, 90°, 180°, 270°
- Emulation: TSPL, EPL, ZPL, DPL
- Dimensions 302,5mm (D) x 234mm (W) x 194,8mm (H)
- Weight 2.6kg

**Package contents**

- 1x Label Printer
- 1x Power supply
- 1x USB cable
- 1x Test label paper
- 2x Label role receptacle
- 1x Cardboard sleeve
- 1x Ribbon
- 1x Ribbon recycling roll
- 2x Ribbon screw
- 1x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	4	18.00	59.00	43.00	64.00	162,368.00
Packaging Unit Inside	1	4.50	0.00	0.00	0.00	0.00
Packaging Unit Single	1	4.50	40.50	27.50	29.00	32,298.80
Net single without Packaging	0	2.60	30.30	23.40	19.50	13,825.90

**More images:**



**Safety notes**

- Do NOT look directly into the LED light.
- Do not look at the light source either directly or using optical aids.
- Do NOT expose the reader to flammable substances.
- Under no circumstances should you attempt to carry out unauthorized repairs to the installed components.
- A socket outlet for the AC power supply should be available and easily accessible near the device. Ensure a stable power supply so that the reader and peripheral devices function correctly.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)