

DIGITUS SOHO PRO wall-mounted enclosure - 483 mm (19") - 540x400 mm (WxD)

DN-49202
EAN 4016032493709



19" 7U wall mounting cabinet, SOHO PRO 370 x 540 x 400 mm, grey

Whether in the home, office or for sub-distribution boards with limited space: With the compact 483 mm (19") solutions from the SOHO PRO series, you can install your network wherever you want. Available in four height units (4U, 7U, 9U, 12U), the wall-mounted enclosures are equipped with a full glass door and a cable entry in the top and bottom. A pair of galvanized 483 mm (19") profile rails labelled with legible height units are installed inside. These can be adjusted in depth. Each cabinet is a robust steel construction made of up to 1.5 mm thick sheet steel. The coloring takes the form of electrostatic powder coating in the standard colors grey (RAL 7035) and black (RAL 9005). The door hinges can be changed. The network enclosures are supplied unassembled in an optimized flat pack. Assembly takes place in just a few steps and is child's play thanks to the enclosed step-by-step instructions.

The DIGITUS® wall-mounted enclosure SOHO PRO series is characterized by its efficient delivery in an optimized flat pack and particularly user-friendly installation.

- Protection class IP20
- Lockable safety glass door
- 200° door opening angle
- 1-point locking on the front door

- 483 mm (19") profile rails mounted at the front inside the enclosure, galvanized
- 483 mm (19") profile rails are adjustable in depth
- 1.1 - 1.5 mm thick sheet steel with a high load-bearing capacity, powder-coated
- Cable entry with plastic cover in the roof and floor
- Ventilation slots for active and passive ventilation
- Installation depth for components max.: 327 mm
- Product dimensions (H x W x D): 370 x 540 x 400 mm
- Cabinet type: Wall mounting cabinet
- Color: light grey, RAL 7035
- Depth: 400 mm
- Front door: Glass door, single opening
- Load capacity: 60 kg
- Side panels: Both sides
- Units: 7
- Width: 540 mm
- IP protection class: IP20
- Mounted: no

Package contents

- Installation set (screws, cage nuts, washers)
- 2x key
- 1x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	9.88	58.00	38.50	17.50	39,077.50
Packaging Unit Inside	1	9.88	58.00	38.50	17.50	39,077.50
Packaging Unit Single	1	9.88	58.00	38.50	17.50	39,077.50
Net single without Packaging	0	9.11	40.00	54.00	37.00	79,920.00

More images:



DN-48002
Wall Mounting Cabinet SOHO PRO
483mm (19") - 540x400mm (WD)

DIGITUS

- Slide the top panel onto the body in the direction of the arrows. Only elements that protrude of the top panel are to be inserted into the upper holes of the body. Insert the top edge of the glass door into the top edge of the top panel. Insert the rear edge of the top panel in the panel gap of the body. Assemble the bottom panel to the body by 4 screws.
- Put the cabinet on the floor. Use the bottom panel to hold the cabinet. Open the recesses of the bottom panel downwards and the recesses of the top panel upwards.
- Show the QR code your camera or mobile the installation manual. Your SOHO cabinet is ready to use.

DN-48002
Wall Mounting Cabinet SOHO PRO
483mm (19") - 540x400mm (WD)

DIGITUS

- Use the 19" SoHo cabinet ear of the body.
- Slide the bottom plate onto the body in the direction of the arrows. To avoid the cabinet from falling the recesses of the bottom plate into the top edge of the body.
- Slide the bottom panel to the body by 4 screws. During the screw process horizontally make sure to insert the 4 screws into the recessed areas. Check the door. The panel should be inserted smoothly. Please check whether the door is closed properly. Please check whether there is no protrusion on the top edge of the glass door.
- Let the body down and bottom panel to be at the installation site. Insert the top hinge pin of the glass door from the edge back of the top panel.