

DIGITUS SOHO PRO wall-mounted enclosure - 483 mm (19") - 540x400 mm (WxD)

DN-49204
EAN 4016032493730



19" 9U wall mounting cabinet, SOHO PRO 460 x 540 x 400 mm, grey

Whether in the home, office or for sub-distribution boards with limited space: With the compact 483 mm (19") solutions from the SOHO PRO series, you can install your network wherever you want. Available in four height units (4U, 7U, 9U, 12U), the wall-mounted enclosures are equipped with a full glass door and a cable entry in the top and bottom. A pair of galvanized 483 mm (19") profile rails labelled with legible height units are installed inside. These can be adjusted in depth. Each cabinet is a robust steel construction made of up to 1.5 mm thick sheet steel. The coloring takes the form of electrostatic powder coating in the standard colors grey (RAL 7035) and black (RAL 9005). The door hinges can be changed. The network enclosures are supplied unassembled in an optimized flat pack. Assembly takes place in just a few steps and is child's play thanks to the enclosed step-by-step instructions.

The DIGITUS® wall-mounted enclosure SOHO PRO series is characterized by efficient delivery in an optimized flat pack and particularly user-friendly installation.

- Protection class IP20
- Lockable safety glass door
- 200° door opening angle
- 1-point locking on the front door

- 483 mm (19") profile rails mounted at the front inside the enclosure, galvanized
- 483 mm (19") profile rails are adjustable in depth
- 1.1 - 1.5 mm thick sheet steel with a high load-bearing capacity, powder-coated
- Cable entry with plastic cover in the roof and floor
- Ventilation slots for active and passive ventilation
- Installation depth for components max.: 327 mm
- Product dimensions (H x W x D): 460 x 540 x 400 mm
- Cabinet type: Wall mounting cabinet
- Color: light grey, RAL 7035
- Depth: 400 mm
- Front door: Glass door, single opening
- Load capacity: 60 kg
- Side panels: Both sides
- Units: 9
- Width: 540 mm
- IP protection class: IP20
- Mounted: no

Package contents

- Installation set (screws, cage nuts, washers)
- 2x key
- 1x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	11.44	58.00	47.50	17.50	48,212.50
Packaging Unit Inside	1	11.44	58.00	47.50	17.50	48,212.50
Packaging Unit Single	1	11.44	58.00	47.50	17.50	48,212.50
Net single without Packaging	0	10.58	40.00	54.00	46.00	99,360.00

More images:



DN-43204
Wall Mounting Cabinet SOHO PRO
483mm (19") - 540x400mm (WD)

DIGITUS

- Slide the top panel into the body, cabinet out of the box.
- Open the top side panels of the body.
- Slide the bottom panel into the body in the direction of the arrows. As soon as the cabinet is inserted, the recesses of the bottom panel into the top panel of the body.
- Fix the bottom panel to the body by the screws. Change the screw panel to the screws to be mounted to all cabinet sides described above. Then, fix the screws to the screws using the provided screws. Please note: The screws must be mounted to the top edge of the cabinet door.
- Use the body filter and bottom panel to fit at the backside. Insert the top hinge on top of the glass into the hinge hole of the top panel.

DN-43204
Wall Mounting Cabinet SOHO PRO
483mm (19") - 540x400mm (WD)

DIGITUS

- Slide the top panel into the body in the direction of the arrows. The bottom side recesses of the top panel will be inserted into the upper holes of the body. Insert the top hinge of the glass into the top hole of the top panel. Insert recesses of the top panel into the panel gap of the body. Assemble the bottom panel to the body by 4 screws.
- Put the cabinet on the floor. The bottom panel marks the ground. Check the accuracy of the bottom panel placement and the recesses of the top panel assembly.
- Close the top cover and screws to fix the ventilation cover. Your SoHo cabinet is ready to use.