

DIGITUS FTTH Enclosure with 2 x LC/APC DX couplers

DN-931096
EAN 4016032494676



FTTH Enclosure, with 2x LC(APC) DX adapter Surface mount

The Fibre wall outlet is designed to be used as an optical telecommunications outlet. It is an ultra compact enclosure for managing up to 4 fibres within the property and can be easily wall mounted providing the connection point for upto 4 end devices. It is pre-assembled with 2 x LC/APC Duplex couplers and offers entry points at the rear, bottom and top for flexible cable entries according to requirement. It efficiently brings together the possibility of fiber splices, terminations, storage and connections in a minimal space. Also the screw holes on the rear allow for easy installation and positioning maintaining the outlet flush to the wall.

FTTH wall outlet designed minimalistically for distribution of up to 4 fibers. The compact protective housing is perfect in FITH and office premise cabling for fiber splices, terminations and connections.

- Design : Wall outlet
- Mounting style : Surface mount

- Transmission technology : Fiber optic
- Integrated splice cassette
- Type of fiber : Singlemode
- Connector interface : LC Duplex
- Connector type : LC/APC
- Number of ports interface : 2
- Number of equipped ports interface : 2
- Cable access/outlet : Rear, top, bottom
- Housing material: PC + ABS
- Protection type: IP45
- Operating temperature: -40°C ~ +85°C
- Color : Pure white
- Dimensions (LxWxH): 104 x 80 x 23 mm
- Weight: 0.07 kg

Package contents

- FTTH enclosure with 2 x LC/APC DX couplers

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	200	18.00	50.00	50.00	28.00	70,000.00
Packaging Unit Inside	1	0.09	3.00	9.00	11.50	310.50
Packaging Unit Single	1	0.09	3.00	9.00	11.50	310.50
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:

