

# DIGITUS

**DK-1511-V-305**  
**EAN 4016032241089**



**DIGITUS CAT 5e U-UTP installation cable, raw length 305m, paper box, AWG 24/1**

- Assortment: Twisted Pair Installation Cables
- Category: CAT 5e
- Shielding: U-UTP, unshielded

- CPR: Eca
- Length: 305 m
- Color: grey
- Jacket: PVC
- Structure: 4 x 2 AWG 24/1, solid twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	2	18.50	42.00	37.00	38.00	59,052.00
Packaging Unit Inside	1	9.25	20.00	35.00	36.00	25,200.00
Packaging Unit Single	1	9.25	20.00	35.00	36.00	25,200.00
Net single without Packaging	1	8.49	20.00	35.00	36.00	25,200.00

**More images:**



**CAT 5e U/UTP Installation Cable, 305m, Simplex, E<sub>ca</sub>**

Produktinformationen Product Information		Physikalische Spezifikationen Physical Properties	
Assortimentsname Assortment Name	DK-1511-V-305 (Simplex, Paper, Grey, 305m)	Farbe Color	Black/Orange/Blue/White
Artikelnummer Article Number	DK-1511-V-305	Leitungsverhalten Conductor	4x2x0,20mm
Hersteller Manufacturer	DIGITUS	Leitungsverhalten Conductor	4x2x0,20mm
Produkttyp Product Type	Installation Cable	Leitungsverhalten Conductor	4x2x0,20mm
Material Material	PVC	Leitungsverhalten Conductor	4x2x0,20mm
Lebensdauer Lifetime	10 years	Leitungsverhalten Conductor	4x2x0,20mm
Abmessungen Dimensions	305m x 20mm x 35mm	Leitungsverhalten Conductor	4x2x0,20mm
Nettogewicht Net Weight	8.49 kg	Leitungsverhalten Conductor	4x2x0,20mm
Bruttogewicht Gross Weight	18.50 kg	Leitungsverhalten Conductor	4x2x0,20mm
Umweltzone Environment	Indoor	Leitungsverhalten Conductor	4x2x0,20mm
CE-Zertifizierung CE Certification	CE	Leitungsverhalten Conductor	4x2x0,20mm
RoHS-Konformität RoHS Compliance	RoHS	Leitungsverhalten Conductor	4x2x0,20mm
WEEE-Konformität WEEE Compliance	WEEE	Leitungsverhalten Conductor	4x2x0,20mm
REACH-Konformität REACH Compliance	REACH	Leitungsverhalten Conductor	4x2x0,20mm
IP-Konformität IP Compliance	IP	Leitungsverhalten Conductor	4x2x0,20mm

Leistungsleistungen Transmission Properties									
MHz	AT	MDT	PK MD	AKA	PK AK	LA	ELVAT	PK ELVAT	
1	1	1	1	1	1	1	1	1	1
10	10	10	10	10	10	10	10	10	10
100	100	100	100	100	100	100	100	100	100
1000	1000	1000	1000	1000	1000	1000	1000	1000	1000
10000	10000	10000	10000	10000	10000	10000	10000	10000	10000
100000	100000	100000	100000	100000	100000	100000	100000	100000	100000

**ETL Intertek**  
 ETL Verified Certificate of Conformance Number: 1611020002241089  
 This certificate certifies that the product conforms to the requirements of the standard as indicated on the certificate.

**CAT 5e**  
**CAT 7**  
**CAT 7 RSHD**  
**CAT 6**  
**CAT 6e**

