

# DIGITUS colored pigtails, LC OM2 50/125 $\mu$ , Simplex

DK-25332-02  
EAN 4016032280163



**FO pigtail set, 12 pcs., LC, MM OM2 50/125  $\mu$  loose buffer, color code DIN IEC 304, 2m**

The DIGITUS® Fiber Optic Colored Pigtails are available as LC Simplex, SC Simplex and ST Simplex version and offer with the classes OS2, OM2, OM3 and OM4 best performance and link quality for your network. The connector conforms acc. IEC 61754-4 2002 and is equipped with a Zirconia ceramic ferrule. The colored buffers are color coded according to IEC 304 (white, violet, turquoise, black, red, pink, orange, gray, green, yellow, brown, blue).

**Future-oriented standards and high-end quality for your network.**

- Standard connector acc. IEC 61754-4 2002
- Operating temperature: -25 °C ... +80 °C
- Storage temperature: -20 °C ... +65 °C
- Insertion loss MM PC: max. 0.4 dB
- Return loss MM PC: > 25 dB

- Zirconia ceramic ferrule
- Simplex OM2 50/125  $\mu$  2 m
- Secondary coating dimensions:  $\varnothing$  0.9  $\pm$  0.1 mm
- Primary coating: Acrylate;  $\varnothing$  250  $\pm$  15  $\mu$ m
- Colored buffer, according to IEC 304 in the colors white, violet, turquoise, black, red, pink, orange, grey, green, yellow, brown, blue
- 12 pcs in package
- Loose buffer
- Boot: single-color
- Cable jacket: LSOH
- Connector 1: LC
- Fiber class: OM2
- Fiber diameter: 50/125 $\mu$
- Mode: Multimode
- Length: 2 m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	160	7.20	41.00	41.00	28.00	47,068.00
Packaging Unit Inside	20	0.90	19.00	19.00	12.00	4,332.00
Packaging Unit Single	1	0.05	17.00	17.00	1.00	289.00
Net single without Packaging	1	0.04	17.00	17.00	1.00	289.00