

# DIGITUS Datatransfer connection cable, D-Sub9/F - D-Sub9/F

AK-610106-020-E  
EAN 4016032301134



**Datatransfer connection cable, D-Sub9 F/F, 2.0m, serial, molded, be**

Datatransfer connection cable, D-Sub9,F/F, 2.0m, serial, molded, be

**Enables a save and stable connection**

**Attributes**

- Assignment: 1:1
- Assortment: Serial Cables
- AWG: 28

- Color cable: beige
- Color connector: beige
- Connector 1: DSUB, 9-pin, jack
- Connector 2: DSUB, 9-pin, jack
- Connector surface: nickel-plated
- Hoods: molded
- Wire material: CU
- Length: 2 m
- Shielding: single shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	120	14.78	32.00	45.00	25.00	36,000.00
Packaging Unit Inside	10	1.23	25.00	25.00	8.00	5,000.00
Packaging Unit Single	1	0.12	1.25	14.00	25.00	437.50
Net single without Packaging	1	0.12	1.25	14.00	25.00	437.50

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.

- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)