

# DIGITUS Datatransfer connection cable, D-Sub9/M - D-Sub9/M

AK-610107-020-E  
 EAN 4016032301165



**Datatransfer connection cable, D-Sub9 M/M, 2.0m, serial, molded, be**

Datatransfer connection cable, D-Sub9,M/M, 2.0m, serial, molded, be

**Enables a save and stable connection**

- Assignment: 1:1
- Assortment: Serial Cables
- AWG: 28
- Color cable: beige

- Color connector: beige
- Connector 1: DSUB, 9-pin, plug
- Connector 2: DSUB, 9-pin, plug
- Connector surface: nickel-plated
- Hoods: molded
- Packaging: Polybag
- Wire material: CU
- Length: 2 m
- Shielding: single shielding

| Logistics                    |              |             |            |            |             |                 |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm <sup>3</sup> |
| Packaging Unit Carton        | 120          | 14.61       | 32.00      | 45.00      | 25.00       | 36,000.00       |
| Packaging Unit Inside        | 1            | 0.12        | 0.00       | 0.00       | 0.00        | 0.00            |
| Packaging Unit Single        | 1            | 0.12        | 1.50       | 14.00      | 25.00       | 525.00          |
| Net single without Packaging | 1            | 0.12        | 1.50       | 14.00      | 25.00       | 525.00          |

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.

- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)