

# DIGITUS DIN-Rail Adapter for 1x Keystone Module

**AN-25184**  
**EAN 4016032305859**



### DIN-Rail adapter for 1x Keystone Module

The DIGITUS® DIN-Rail adapter function as adapter for the installation of Keystone Modules. They are available as 1-port or 2-port version.

- Layout keystone entry: 45° outlet
- Area of application: Electrical distribution box
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C

- General properties:
- Suitable for installation on DIN-rail in electrical distribution boxes
- Technical properties:
- Housing material: Stainless steel
- Physical properties:
- Operation temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	500	12.00	33.00	26.00	32.00	27,456.00
Packaging Unit Inside	20	0.48	25.00	6.00	6.00	900.00
Packaging Unit Single	1	0.02	9.00	7.00	3.00	189.00
Net single without Packaging	1	0.02	9.00	7.00	3.00	189.00

### More images:



### Safety notes

- Observe the specifications of the raw cable manufacturer during installation

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)