

DIGITUS Industrial mini GBIC (SFP) Module, 1.25 Gbps, 0.55km

DN-81010

EAN 4016032307570



1.25 Gbps SFP Module, Multimode, Industrial ver. LC Duplex Connector, 850nm, up to 550m

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- High quality and excellent reliability
- 1.25 Gbps Maximum Data Rate
- Compliant to IEEE 802.3z Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant

- Hot pluggable
- Connector: 1x LC Duplex
- 1000Base-SX - For Short Haul
- Wavelength: 850nm
- Transmission power: minimum -8 dBm, maximum -3 dBm
- Sensitivity Receiving Power: Minimum -20 dBm
- For a Distance of up to 0.55km
- Suitable for 50/125µm and 62.5/125µm multimode fiber cables
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: -40 °C - +85 °C

Attributes


- Mode: Multimode
- Connector: LC
- Distance (km): 0.5
- Wavelength: 850 nm
- DDM Support: no
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Universal (MSA), Cisco
- Ethernet speed: Fast Ethernet

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	240	8.50	50.00	29.00	54.50	79,025.00
Packaging Unit Inside	30	1.06	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.04	10.00	7.00	2.00	140.00
Net single without Packaging	1	0.02	10.00	7.00	2.00	140.00

More images:



Product Number	Form Factor	Speed	Distance	Connector	Wavelength	Operating Temperature	Industrial Version
DM-4001	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4002	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4003	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4004	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4005	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4006	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4007	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4008	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4009	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4010	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4011	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4012	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4013	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4014	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4015	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4016	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4017	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4018	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4019	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4020	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4021	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4022	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4023	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4024	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4025	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4026	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4027	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4028	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4029	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4030	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4031	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4032	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4033	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4034	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4035	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4036	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4037	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4038	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4039	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4040	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4041	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4042	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4043	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4044	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4045	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4046	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4047	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4048	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓
DM-4049	40G QSFP+	40 Gbps	2 km	LC MPO	1310nm	0°C to 70°C	✓
DM-4050	40G QSFP+	40 Gbps	2 km	LC MPO	1550nm	0°C to 70°C	✓

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com