

# DIGITUS UAE Modular Connection Helix Cable

AK-460101-020-S  
 EAN 4016032330110



**UAE connection cable, RJ10 M/M, 2.0m, CU, 4x7x0,12mm, flat, helic, bl**

This modular helix cable can be used to connect of the receiver/earphone with the telephone and serves as an ideal replacement of too short / long or defective original cables.

**High eleastic and flexible**

- Modular plug RJ10, 4P4C <=> Modular plug RJ10, 4P4C
- Plastic plugs, transparent
- Assignment: 1:1
- 4-wire helix cable
- Color: Black
- Assortment: Telecommunication Cables
- Length: 2 m

| Logistics                    |              |             |            |            |             |                 |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm <sup>3</sup> |
| Packaging Unit Carton        | 400          | 13.33       | 44.50      | 40.00      | 26.00       | 46,280.00       |
| Packaging Unit Inside        | 10           | 0.33        | 19.50      | 13.50      | 6.00        | 1,579.50        |
| Packaging Unit Single        | 1            | 0.03        | 1.50       | 14.00      | 20.00       | 420.00          |
| Net single without Packaging | 1            | 0.03        | 1.50       | 14.00      | 20.00       | 420.00          |

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable

- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)