

DIGITUS Network Rack Dynamic Basic Series - 600x600 mm (WxD)

DN-19 42U-6/6-DB
EAN 4016032336747



42U network rack, Dynamic Basic 2040x600x600 mm, color black (RAL 9005)

The network cabinets from the Dynamic series were developed for easy and especially cost-optimized network expansion. Clever placement of the cable inlets ensures effortless installation for every application. They are located at the back center in the floor structure, protected by a bolted cover plate. Cabinets from a width of 800 mm also feature cable inlets with a plastic cover to the left and right. These are also integrated into the roof (1 x for 600 mm cabinet width, 3 x for 800 mm cabinet width). To accommodate a fan module, the roof structure is also equipped with a pre-cut area. Two pairs of galvanized 483 mm (19") profile rails labeled with rack units readable in both directions are installed on the inside. Their depth is adjustable and they are connected to additional depth bars in the cabinet. Each cabinet is made of up to 1.5 mm thick sheet steel. Coloring is done with electrostatic powder coating in the standard colors gray (RAL 7035) or jet black (RAL 9005). Removable side and back walls as well as lockable and removable front door improve accessibility. The door hinges can be switched. Furthermore, the cabinets can be completely dismantled if necessary due to their collapsible design.

The DIGITUS® Dynamic Basic Series is made for high demand IT-Infrastructure Solutions - designed and developed on highest standard in Germany

- Safety class rating IP20
- Lateral metal struts front door with safety glass
- Lock system with pivot lever on front door
- 120° door opening angle on the front door
- 1-point-locking-mechanism on the front door
- Rear wall and side panels are lockable and detachable

- incl. 4 pieces of leveling feet already pre-configured under the rack
- 483 mm (19") profile rails mounted on the front- and rear side inside of the rack, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height unit marking
- Base with punched out cable entry, covered with screwed metal plate
- Roof with punched out cable entries with plastic covers
- Roof is prepared for fan units (punched out entries)
- Several earthing points for rack components
- Incl. installation set (screws, cage nuts, washers)
- Rack is completely mounted
- Equipment mounting depth min.-max.: 290-550 mm
- Cabinet type: Network cabinet
- Color: black, RAL 9005
- Depth: 600 mm
- Front door: Glass door, single opening
- Load capacity: 600 kg
- Rear door: Rear panel with lock, detachable
- Side panels: Both sides
- Units: 42
- Width: 600 mm
- IP protection class: IP20
- Mounted: yes

Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- 2 x keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	73.00	65.00	65.00	209.00	883,025.00
Packaging Unit Inside	1	73.00	65.00	65.00	209.00	883,025.00
Packaging Unit Single	1	73.00	65.00	65.00	209.00	883,025.00
Net single without Packaging	1	70.05	65.00	65.00	209.00	883,025.00

More images:

