

DIGITUS Cat.6A U/FTP installation cable

DK-1624-A-VH-1
EAN 4016032344131



CAT 6A U-FTP installation cable, 500 MHz Dca (EN 50575), AWG 23/1, 100 m paper box,

DIGITUS Category 6A F-FTP installation cables are manufactured and tested to the ISO/IEC 11801, TIA/586-C.2 and YD/T1019 Category 6A specifications. Every cord consists of 8 color coded AWG 23 polyethylene insulated conductors. The conductors are twisted together to form 4 pairs with varying lay lengths. Printing details along the outer sheath includes the brand name and item code. The cable is packed in a paper pullout box which makes the installation easy. Moreover it is reducing waste.

Future-oriented standards and high-end quality for your network.

- 25 Year System Warranty
- Halogen free outer sheath
- Category 6A compliant, ISO/IEC 11801, TIA/586-C.2, EN 50173
- Stressless paper pullout box
- AWG 23 conductor
- 500 MHz

- Basic conductor: Solid AWG 23/1
- System/s of AVCP: AVCP 3
- Insulation: SFS-PE
- Total number of insulated conductors: 8, twisted in 4 pairs
- Color code: blue-white, orange-white, green-white, brown-white
- Individual pair shielding: Aluminum foil, providing 100 % coverage
- Outer jacket: LSOH
- Storage temperature: -20 °C - +60 °C
- Installation temperature: 0 to +50 °C
- Standard of flame retardancy: IEC 60332-1-1 (1,2)(2004-07)
- Color: Light blue (RAL 5012)
- Category: CAT 6A
- Shielding: U-FTP, pairs in metal foil
- CPR: Dca
- Length: 100 m
- Color: light-blue
- Jacket: LSOH
- Structure: 4 x 2 AWG 23/1, solid twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	1	-0.30	0.00	0.00	0.00	0.00