

1

# **DIGITUS USB Type-C adapter, Type-C to A**

AK-300506-000-S EAN 4016032370802





### USB Type-C adapter, type C to A M/F, 3A, 5GB, 3.0 Version, bl

Compact adapter for connection of devices with USB Type-C interface (e. g. Smart Phone, Notebook or Tablet) to the power adapter, PC or Hub by usage of an USB 2.0/3.0 A to A connection cable. Datatransferrate up to 5 Gbps (Super Speed).

## Type-C connector can be used in both directions

- SuperSpeed data transmissions up to 5 Gbit/s - 10x faster than USB 2.0
- Supports up to 3A Power supply
- Support of USB PD (Power Delivery) specification
- Type-C connector can be used in both directions

. Downward compatible to USB 2.0 and 1.1

## Attributes

- Assortment: USB Cables •
- Color connector: black
- Connector 1: USB C, plug
- Connector 2: USB A, jack Connector surface: nickel-plated
- Hoods: molded
- USB compliance: USB Type-C<sup>™</sup> •
- Shielding: Unshielded . .
- USB-C Products: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1000	6.60	44.00	33.00	22.00	31,944.00
Packaging Unit Inside	10	0.07	8.50	6.00	8.00	408.00
Packaging Unit Single	1	0.01	2.00	0.50	3.50	3.50
Net single without Packaging	1	0.00	2.00	0.50	3.50	3.50

### More images:









- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

## EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com