


DIGITUS USB Type-C connection cable

DB-300136-010-S
EAN 4016032383772



USB Type-C connection cable, type C to A M/M, 1.0m, 3A, 5GB, 3.0, bl

For connecting external USB end devices (with C socket, e.g. tablet or smartphone) to the USB host (e.g. PC, notebook or USB hub). Transfer rate up to 5 Gbps (super speed 10x faster than USB 2.0). Supports power supply up to 3A with USB 3.0 features. Supports PD (Power Delivery specifications).

For super-fast synchronization and charging

- SuperSpeed data transfers up to 5 Gbit/s - 10 times faster than USB 2.0
- Supports up to 3A power supply
- Supports the USB PD (power delivery) specification with 60W (20V/3A)
- Type C plug can be used on both sides


- Backwards compatible with USB 2.0 and 1.1

Attributes

- Assortment: USB Cables
- AWG: 24/28
- Color cable: black
- Color connector: black
- Connector 1: USB C, plug
- Connector 2: USB A, plug
- Connector surface: nickel-plated
- Hoods: molded
- Wire material: CU
- Length: 1 m
- Shielding: Double shielding
- USB-C Products: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	80	11.20	24.00	16.00	28.00	10,752.00
Packaging Unit Inside	20	2.80	23.50	7.50	2.30	405.38
Packaging Unit Single	1	0.14	9.00	9.00	1.50	121.50
Net single without Packaging	1	0.11	9.00	9.00	1.50	121.50

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com