

# DIGITUS USB Type-C extension cable, Type-C - C

AK-300210-015-S  
EAN 4016032455301



**USB Type-C extension cable, Type C M/F, 1.5m, 3A, 480MB, Version 2.0, bl**

This USB Type-C extension cable allows to extend the usage distance of the type C interface at the Notebook, Tablet, Smartphone or at the docking station.

**Extend your original Type-C™ port on your MacBook or other device to a suitable location**

- Power supply support up to 20V/3A, 60W

- AWG: 22
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: USB-C jack
- Connector surface: nickel-plated
- USB compliance: USB 2.0
- Length: 1.5 m
- Shielding: Double shielding
- USB-C Products: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	300	14.80	45.00	34.00	28.00	42,840.00
Packaging Unit Inside	10	0.49	25.00	4.00	22.00	2,200.00
Packaging Unit Single	1	0.05	12.00	1.00	16.00	192.00
Net single without Packaging	1	0.05	12.00	1.00	16.00	192.00

**More images:**





**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)